



**Document of Performance
According to Regulation (EU) 305/2011**

Aduro 1.1, Aduro 1.1SK, Aduro 1.2, Aduro 1.3, Aduro 1.4, Aduro 1.5		DoP No: 1-1 0005
Roomheater burning solid fuel <u>wi</u> th <u>o</u> ut hot water supply.		
EN 13240:2001/A2:2004/AC:2007		
Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk , info@aduro.dk , Tel.: +45 70274703.		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.		
performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> : RRF- 40 12 3010 / 40 15 4020 300-ELAB-1199-NS		
Declared performance		
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials Distance marked with * is for installation with isolated pipe	Minimum distances, in mm rear = 170/ *120 sides = 450 front = 1000 corner = 300	
Risk of burning fuel falling out	Pass	
Emission of combustion products	CO[0,06 %]	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum water operating pressure	NPD	
Flue gas temperature at nominal heat output	T [289 °C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output	6 kW	
Room heating output	6 kW	
Water heating output	"" kW	
Energy efficiency	η [81,2 %]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Hasselager, 29-07-2015

.....