Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: EGLO			
Supplier's address:	EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT		

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Anti-glare shield:	No No Product para	Dimmable:	No
Anti-glare shield:		Dimmable:	No
	No		
High luminance light source:			
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Light source cap-type (or other electric interface)	-		
Lighting technology used:	LED	Non-directional or directional:	DLS

		i rodact parar		I
Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	nption in on- 00 h), rounded st integer	4	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	3,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	1	Spectral power dis-	See image
sions without	Width	10	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	250	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	52
		Chromaticity coordi-	0,382
		nates (x and y)	0,379
Parameters for directional light sources:			
Peak luminous intensity (cd)	290	Beam angle in degrees, or the range of beam angles that can be set	115
Parameters for LED and OLED light sources:			
R9 colour rendering index value	4	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

