


1	General information	Supplier's name or trade mark			
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN		
3		Model Identifier - Luminaire Supplier reference	CE25613H10-WH.CE25613H10-BL		
4		Light sources maker model	605-01#		
5		Date of placement on the market	01/09/2021		
6	Type of light source:	Lighting technology used:	LED		
7		Light source cap type (or other electric interface)	no		
8		Non-directional (NDLS) or directional (DLS):	NDLS		
9		Mains (MLS) or non-mains (NMLS):	NMLS		
10		Connected light source (CLS):	no		
11		Colour-tuneable light source:	no		
12		Envelope:	no		
13		High luminance light source:	no		
14		Anti-glare shield:	no		
15		Dimmable:	no		
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h)	5	kWh/1000h	
17		Energy efficiency class	E		
18		Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm	580	360	
19		Correlated colour type	single value		
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3000	K	
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal	4.3	W	
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal	0.00	W	
23		Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0.00	W	
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)			
26		Height (mm)	5.00	mm	
27		Width (mm)	586.00	mm	
28		Depth (mm)	0.15	mm	
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg))			
30		Claim of equivalent power	yes		
31		If yes, equivalent power (W)	46	W	
32		Chromaticity coordinates (x and y)	0.440; 0.403		
33		Parameters for directional light sources:	Peak luminous intensity (cd)		cd
34	Beam angle in degrees (no decimal), or the range of beam angles that can be set		0	Degrees	
35	Parameter for LED and OLED light sources:	R9 colour rendering index value	1		
36		Survival factor rounded to the second decimal (>0.xx)	0.90		
37		Lumen maintenance factor rounded to the second decimal (>0.xx)	0.95		
38	Parameters for LED and OLED mains lights sources:	displacement factor (cos ϕ_1) rounded to the second decimal	0.00		
39		Colour consistency in McAdam ellipses	6.0		
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.			
41		If yes then replacement claim (W) (no decimal)	0.0	W	
42		Flicker metric (Pst LM) rounded to the first decimal	0.0		
43		Stroboscopic effect metric (SVM) rounded to the first decimal	0.0		
44	Technical documentation name (in case of light source product)				
45	Light source removing instruction name (in case of containing product)		CE25613H10-spectral power distribution.jpg		

1	General information	Supplier's name or trade mark	INSPIRE
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS0001, 59790 RONCHIN
3		Model Identifier - Luminaire Supplier reference	CE25613H10 - WH, CE25613H10 - BL
4		Light sources maker model	605-01#

Instructions on how to remove lighting control parts and/or non-lighting parts, if any, or how to switch them off or minimise their power consumption during light source testing

	Explanation of the step	Pictures	Tools
Step 1	Loosen the screws with a screwdriver		screwdriver
Step 2	Use scissors to cut the wire		scissors
Step 3	The screwdriver removes the plastic cover		screwdriver
Step 4	Take out the LED module		hand
Step 5	The LED module is fixed to the aluminum radiator		hand
Step 6	Light source for SLR testing		hand
Step 7			
Step 8			
Step 9			