


 PRODUCT INFORMATION SHEET (ANNEX 5)		Creation date (dd/mm/yyyy) : 2021/7/16		
		Last update date (dd/mm/yyyy) : 2021/7/16		
1	General information	Supplier's name or trade mark		
2		Supplier's address ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN		
3		Model Identifier - Luminaire Supplier reference DE26711-WHITE,DE26711-BLACK		
4		Light sources maker model 609-02#		
5		Date of placement on the market 01/09/2021		
6	Type of light source:	Lighting technology used: LED		
7		Light source cap type (or other electric interface) no		
8		Non-directional (NDLS) or directional (DLS): NDLS		
9		Mains (MLS) or non-mains (NMLS): NMLS		
10		Connected light source (CLS): no		
11		Colour-tuneable light source: no		
12		Envelope: no		
13		High luminance light source: no		
14		Anti-glare shield: no		
15	Dimmable: no			
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h) 6 kWh/1000h		
17		Energy efficiency class D		
18		Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm 820 lm in sphere 360		
19		Correlated colour type range		
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set 3000/6500 K		
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal 5.6 W		
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal 0.00 W		
23		Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal 0.00 W		
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set 80		
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)		
26		Height (mm)	29.00	mm
27		Width (mm)	180.00	mm
28		Depth (mm)	1.00	mm
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)) 		
30		Claim of equivalent power yes		
31		If yes, equivalent power (W) 61 W		
32		Chromaticity coordinates (x and y) 0.440; 0.403 or 0.313; 0.337		
33	Parameters for directional light sources:	Peak luminous intensity (cd) cd		
34		Beam angle in degrees (no decimal), or the range of beam angles that can be set 0 Degrees		
35		R9 colour rendering index value 2		
36	Parameter for LED and OLED light sources:	Survival factor rounded to the second decimal (>0.xx) 0.90		
37		Lumen maintenance factor rounded to the second decimal (>0.xx) 0.95		
38		displacement factor (cos ϕ_1) rounded to the second decimal 0.00		
39	Parameters for LED and OLED mains lights sources:	Colour consistency in McAdam ellipses 6.0		
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		
41		If yes then replacement claim (W) (no decimal) 0.0 W		
42		Flicker metric (Pst LM) rounded to the first decimal 0.0		
43		Stroboscopic effect metric (SVM) rounded to the first decimal 0.0		
44	Technical documentation name (in case of light source product)			
45	Light source removing instruction name (in case of containing product) DE26711-spectral power distribution.jpg			

LIGHT SOURCE REMOVING INSTRUCTION

Creation date (dd/mm/yyyy) :

2021/7/16

Last update date (dd/mm/yyyy) :

2021/7/16

1	General information	Supplier's name or trade mark	INSPIRE
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS0001, 59790 RONCHIN
3		Model Identifier - Luminaire Supplier reference	DE26711 - WHITE, DE26711 - BLACK
4		Light sources maker model	609-02#

Instructions on how to remove lighting control parts and/or non-lighting parts, if any, or how to switch them off or minimise their power consumption during light source testing

	Explanation of the step	Pictures	Tools
Step 1	The screwdriver removes the plastic cover		screwdriver
Step 2	Light source for SLR testing		scissors
Step 3			
Step 4			
Step 5			
Step 6			
Step 7			
Step 8			
Step 9			