

# Zeus



## Caratteristiche del prodotto:

- Driver integrato
- Materiale: ABS
- Installazione: attacco a telaio

## Applicazione:



## Finitura:



Cromo lucido

## Alimentazione:



220-240 V

## Sorgente:



LED



## DISEGNI TECNICI



## SPECIFICHE

| CODICE        | DIMENSIONI (mm)  | VOLT    | WATT | LUMEN | COLORE  |
|---------------|------------------|---------|------|-------|---------|
| SL-2828/20/6K | 200 x 74 x 113,6 | 220-240 | 3    | 300   | 6000° K |
| SL-2828/20/4K | 200 x 74 x 113,6 | 220-240 | 3    | 300   | 4000° K |
| SL-2828/30/6K | 300 x 74 x 113,6 | 220-240 | 4,5  | 450   | 6000° K |
| SL-2828/30/4K | 300 x 74 x 113,6 | 220-240 | 4,5  | 450   | 4000° K |
| SL-2828/40/6K | 400 x 74 x 113,6 | 220-240 | 6    | 600   | 6000° K |
| SL-2828/40/4K | 400 x 74 x 113,6 | 220-240 | 6    | 600   | 4000° K |
| SL-2828/50/6K | 500 x 74 x 113,6 | 220-240 | 7,5  | 750   | 6000° K |
| SL-2828/50/4K | 500 x 74 x 113,6 | 220-240 | 7,5  | 750   | 4000° K |
| SL-2828/60/6K | 600 x 74 x 113,6 | 220-240 | 9    | 900   | 6000° K |
| SL-2828/60/4K | 600 x 74 x 113,6 | 220-240 | 9    | 900   | 4000° K |