



Illustrative picture

SPECIFICS

Description	Product type	Horizontal panel interlocked socket 50/60 Hz IP67
	Article code	14.3216B6
	Commercial Series	SERIES 14 IEC 309 IP67

General Data	Poles	N° 2P+E	Type of material	Abs / Nylon / Rubber
	Current	A 16	Dimensional stability	°C -25 / +70
	Voltage	V~ 200-250	Resistance glow wire test	°C +650 / +850
	Earth contact position	h 6		
	Degree of protection	IP 67		
	Impact Resistance	IK 8		
	Insulation Resistance	MΩ >10		

Behaviour with chemical and atmospheric agents

Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article	/	/	/
	Package innerbox	/	/	/
	Packaging	/	/	/

Dimensions		<table border="1"> <thead> <tr> <th>Amp</th> <th colspan="3">16A</th> <th colspan="3">32A</th> </tr> <tr> <th>Poles</th> <th>3</th> <th>4</th> <th>5</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>60</td> <td>68</td> <td>76</td> <td>81</td> <td>81</td> <td>89</td> </tr> <tr> <td>B</td> <td>57</td> <td>57</td> <td>58</td> <td>69</td> <td>69</td> <td>70</td> </tr> </tbody> </table>	Amp	16A			32A			Poles	3	4	5	3	4	5	A	60	68	76	81	81	89	B	57	57	58	69	69	70
	Amp	16A			32A																									
Poles	3	4	5	3	4	5																								
A	60	68	76	81	81	89																								
B	57	57	58	69	69	70																								



Reg. A.E.E n° IT17100000010057

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

DATA	RESPONSABILE TECNICO
24/03/2021	<i>Romano Rosi</i>