



ASSEMBLY AND AFTERCARE GUIDE

NAME OF PRODUCT	COMPOSITE DECK TILE 4L
COLOURS	CHOCOLATE/ DARK GREY/ GREY/TEAK/REDWOOD
BRAND	ADEO
ADEO REFERENC CODE	82754057/ 82754058/ 82754059/ 82754060/ 82754061
EAN CODE	3276007184136/ 3276007184143/ 3276007184150/ 3276007184167/3276007184174
ASSEMBLY	<p>Check the tiles before assembly. Any damage and irregularities should be reported to the seller before assembly. Starting the assembly is considered as acceptance of the technical condition and appearance of the product.</p> <ol style="list-style-type: none"> Deck tiles should be laid on a flat, hard and stable base (e.g. concrete floors, ceramic deck tiles, paving bricks, etc.). Ensure an appropriate surface slope (at least 1 cm over 2 metres) to aid the water run-off out of the decking area. Do not lay deck tiles directly on the ground. Assembly on an unsuitable base may reduce product resistance and strength, and lead to damage. Plan the layout of the deck tiles based on the deck surface measurements. Filling 1 m² of a deck should take up about 11 tiles. Clean the base thoroughly before the deck tiles assembly. Start the deck tiles assembly from the house side. It is possible to cut the tiles to size. To do this, use general purpose wood cutting tools.
AFTERCARE	<p>Composite deck tiles require no maintenance, impregnation or painting.</p> <p>Composite deck tiles are very easy to maintain, but they should be taken care of and cleaned regularly. Cleaning composite tiles is very simple and does not require any special measures. Ordinary household appliances are enough. Day-to-day care of the decking involves removing dirt, sand, leaves, mud with a broom and some water.</p> <p>For heavier dirt, you can achieve a better effect with a rice root brush, water with mild detergent (e.g. dish washing liquid) or a pressure washer. Fat or oil stains should be removed as quickly as possible, never allowing them to dry. For particularly heavy dirt that is difficult to remove, use a copper wire brush or fine grit sandpaper and clean in the direction of the grooves on the lamellas. This should be carried out very carefully so as to avoid damaging the grooves or altering their dimensions.</p> <p>In order to determine whether the cleaning and stain removal method or product will not cause undesired damage or colour changes, it is recommended to perform prior tests.</p> <p>In the initial period of use, stains may appear on composite tiles when the water dries. This is a natural and transient process that should disappear after a few weeks.</p>
UPDATE	16.11.2020