

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 1 of 12

Print date: 04/09/2020

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: MIKADO FRUTOS ROJOS
Product Code: 048556

1.2 Relevant identified uses of the substance or mixture and uses advised against.

air freshener

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **Jesus Gómez S.L.**
Address: Germanells, 8 Polígono Industrial Rafelbuñol
City: Rafelbuñol
Province: Valencia
Telephone: 961410436 / 609032099
Fax: 961410443
E-mail: regulatory@flormayo.com
Web: www.flormayo.com

1.4 Emergency telephone number: 915620420 (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Flam. Liq. 2 : Highly flammable liquid and vapour.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H225 Highly flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.

P statements:

P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P273 Avoid release to the environment.
P370+P378 In case of fire: Use... to extinguish.
P501 Dispose of contents/container to ...

EUH statements:

EUH208 Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 2 of 12

Print date: 04/09/2020

EUH208	Contains Linalool; 3,7-dimethyl- 1,6-octadien-3-ol; dl-linalool. May produce an allergic reaction.
EUH208	Contains Orange oil, sweet. May produce an allergic reaction.
EUH208	Contains p-tert-Butyl-alpha-methylhydrocinnamic aldehyde (BMHCA, Lilial, Lysmeral). May produce an allergic reaction.

2.3 Other hazards.

The product may have the following additional risks:

Not apply

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-002-00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01-2119457610-43-XXXX	[1] ethanol, ethyl alcohol	50 - 75 %	Flam. Liq. 2, H225	-
CAS No: 34590-94-8 EC No: 252-104-2 Registration No: 01-2119450011-60-XXXX	[1] (2-methoxymethylethoxy)propanol	2.5 - 25 %	-	-
CAS No: 928-96-1 EC No: 213-192-8	cis-3-Hexenol	1 - 10 %	Eye Irrit. 2, H319 - Flam. Liq. 3, H226	-
CAS No: 4940-11-8 EC No: 225-582-5	Ethyl maltol	1 - 2.5 %	Acute Tox. 4, H302	-
CAS No: 134-20-3 EC No: 205-132-4	Methyl anthranilate	1 - 10 %	Eye Irrit. 2, H319	-
Index No: 601-029-00-7 CAS No: 5989-27-5 EC No: 227-813-5 Registration No: 01-2119529223-47-XXXX	(R)-p-mentha-1,8-diene, d-limonene	0.25 - 1 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 128-37-0 EC No: 204-881-4 Registration No: 01-2119565113-46-XXXX	[1] 2,6-di-tert-butyl-p-cresol	0.25 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 3 of 12

Print date: 04/09/2020

CAS No: 8008-57-9 EC No: 232-433-8	Orange oil, sweet	0.25 - 1 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 603-235-00-2 CAS No: 78-70-6 EC No: 201-134-4 Registration No: 01-2119474016-42-XXXX	Linalool, 3,7-dimethyl- 1,6-octadien-3-ol, dl-linalool	0.1 - 1 %	Skin Sens. 1B, H317	-
CAS No: 80-54-6 EC No: 201-289-8 Registration No: 01-2119485965-18-XXXX	p-tert-Butyl-alpha-methylhydrocinnamic aldehyde (BMHCA, Lilial, Lysmeral)	0.1 - 1 %	Acute Tox. 4, H302 - Aquatic Chronic 2, H411 - Repr. 2, H361 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(*): The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 4 of 12

Print date: 04/09/2020

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 5 of 12

Print date: 04/09/2020

oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not apply

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
ethanol, ethyl alcohol	64-17-5	United Kingdom [1]	Eight hours	1000	1920
			Short term		
		Éire [2]	Eight hours		
			Short term	1000	
		United States [3] (Cal/OSHA)	Eight hours	1000	
			Short term		
		United States [4] (NIOSH)	Eight hours	1000	
			Short term		
		United States [5] (OSHA)	Eight hours	1000	1900
			Short term		
(2-methoxymethylethoxy)propanol	34590-94-8	European Union [6]	Eight hours	50 (skin)	308 (skin)
			Short term		
		United Kingdom [1]	Eight hours	50	308
			Short term		
		Éire [2]	Eight hours	50	308
			Short term		
		United States [3] (Cal/OSHA)	Eight hours	100	
			Short term	150	
		United States [4] (NIOSH)	Eight hours	100	
			Short term	150	
United States [5] (OSHA)	Eight hours	100	600		
	Short term				
2,6-di-tert-butyl-p-cresol	128-37-0	United Kingdom [1]	Eight hours		10
			Short term		
		Éire [2]	Eight hours		2
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[6] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Long-term, Systemic effects	950 (mg/m ³)
(R)-p-mentha-1,8-diene, d-limonene CAS No: 5989-27-5 EC No: 227-813-5	DNEL (Workers)	Inhalation, Long-term, Systemic effects	33,3 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 6 of 12

Print date: 04/09/2020

2,6-di-tert-butyl-p-cresol CAS No: 128-37-0 EC No: 204-881-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	3,5 (mg/m ³)
p-tert-Butyl-alpha-methylhydrocinnamic aldehyde (BMHCA, Lilial, Lysmeral) CAS No: 80-54-6 EC No: 201-289-8	DNEL (Workers)	Inhalation, Long-term, Systemic effects	0,44 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DREL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	Fresh water	0,96 (mg/L)
	Marine water	0,79 (mg/L)
	aqua (intermittent releases)	2,75 (mg/L)
	Soil	0,63 (mg/kg soil dw)
	sediment (freshwater)	3,6 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	air freshener		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.		
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 7 of 12

Print date: 04/09/2020

Skin protection:

PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Transparent liquid with characteristic odour

Colour: Rojo

Odour: Característico

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: N.A./N.A.

Flash point: 16 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: N.A./N.A.

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 8 of 12

Print date: 04/09/2020

- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- CO_x (carbon oxides).
- Organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Oral) = 31.686 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 9 of 12

Print date: 04/09/2020

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	-0,3	-	-	Very low
(R)-p-mentha-1,8-diene, d-limonene CAS No: 5989-27-5 EC No: 227-813-5	4,83	-	-	High

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 10 of 12

Print date: 04/09/2020

14.1 UN number.

UN No: UN1993

14.2 UN proper shipping name.

Description:

ADR: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / CIS-3-HEXENOL), 3, PG III, (D/E)

IMDG: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / CIS-3-HEXENOL), 3, PG III

ICAO/IATA: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / CIS-3-HEXENOL), 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.


Marine pollutant: No

14.6 Special precautions for user.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 84,209 %

VOC content: 703,294 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

The supplier has carried out a Chemical Safety Assessment for the substance/mixture.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 28/02/2020

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 11 of 12

Print date: 04/09/2020

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Repr. 2 : Reproductive toxicant, Category 2
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
AWSV:	Facility Regulations for handling substances that are hazardous for the water.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
Log Pow:	Logarithm of the partition octanol-water.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID:	Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK:	Water hazard classes.

Key literature references and sources for data:

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

048556-MIKADO FRUTOS ROJOS



JESÚS GÓMEZ, S.L.

Version 1 **Date of compilation: 28/02/2020**

Version 2 (replaces version 1)

Revision date: 04/09/2020

Page 12 of 12

Print date: 04/09/2020

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.