

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 1 of 15

Print date: 12/07/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS
Product Code: 049706
UFI: JFG0-00J7-C00V-WQV4

1.2 Relevant identified uses of the substance or mixture and uses advised against.

air freshener

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **Jesus Gómez S.L.**
Address: Germanells, 8 Polígono Industrial Rafelbuñol
City: Rafelbuñol
Province: Valencia
Telephone: 961410436 / 609032099
Fax: 961410443
E-mail: regulatory@flormayo.com
Web: www.flormayo.com

1.4 Emergency telephone number: 915620420 (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Flam. Liq. 2 : Highly flammable liquid and vapour.

Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

P statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 2 of 15

Print date: 12/07/2021

P273 Avoid release to the environment.
P370+P378 In case of fire: Use extinguisher powder or CO2 to extinguish.
P501 Dispose of contents and container in accordance with local and national regulations.

EUH statements:

EUH208 Contains Geraniol. May produce an allergic reaction.
EUH208 Contains Linalyl acetate. May produce an allergic reaction.
EUH208 Contains alpha-iso-Methylionone. May produce an allergic reaction.

Contains:

(R)-p-mentha-1,8-diene, d-limonene
Linalool, 3,7-dimethyl- 1,6-octadien-3-ol, dl-linalool
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (OTNE)

2.3 Other hazards.

The product may have the following additional risks:
Not apply

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 603-002-00-5 CAS No: 64-17-5 EC No: 200-578-6 Registration No: 01-2119457610-43-XXXX	[1] ethanol, ethyl alcohol	50 - 75 %	Flam. Liq. 2, H225	-
CAS No: 100-79-8 EC No: 202-888-7 Registration No: 01-2120066005-66-XXXX	2,2-dimethyl-1,3-dioxolan-4-ylmethanol	10 - 25 %	Eye Irrit. 2, H319	-
CAS No: 34590-94-8 EC No: 252-104-2 Registration No: 01-2119450011-60-XXXX	[1] (2-methoxymethylethoxy)propanol	2.5 - 10 %	-	-
Index No: 601-029-00-7 CAS No: 5989-27-5 EC No: 227-813-5 Registration No: 01-2119529223-47-XXXX	(R)-p-mentha-1,8-diene, d-limonene	1 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
Index No: 603-235-00-2 CAS No: 78-70-6 EC No: 201-134-4 Registration No: 01-2119474016-42-XXXX	Linalool, 3,7-dimethyl- 1,6-octadien-3-ol, dl-linalool	1 - 2.5 %	Skin Sens. 1B, H317	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 3 of 15

Print date: 12/07/2021

CAS No: 140-11-4 EC No: 205-399-7 Registration No: 01-2119638272-42-XXXX	[1] Benzyl acetate	1 - 25 %	Aquatic Chronic 3, H412	-
CAS No: 18479-58-8 EC No: 242-362-4 Registration No: 01-2119457274-37-XXXX	Dihydromyrcenol (2,6-Dimethyloct-7-en-2-ol)	1 - 10 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
CAS No: 54464-57-2 EC No: 259-174-3	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (OTNE)	1 - 2.5 %	Aquatic Chronic 1, H410 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 63500-71-0	Tetrahydro-2-isobutyl-4-methyl-pyran-4-ol	1 - 10 %	Eye Irrit. 2, H319	-
CAS No: 106-24-1 EC No: 203-377-1 Registration No: 01-2119552430-49-XXXX	Geraniol	0.1 - 1 %	Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 112-53-8 EC No: 203-982-0 Registration No: 01-2119485976-15-XXXX	Dodecanol (Alcohol C12)	0.1 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 2, H411 - Eye Irrit. 2, H319	-
CAS No: 115-95-7 EC No: 204-116-4 Registration No: 01-2119454789-19-XXXX	Linalyl acetate	0.1 - 1 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1B, H317	-
CAS No: 127-51-5 EC No: 204-846-3	alpha-iso-Methylionone	0.1 - 1 %	Aquatic Chronic 2, H411 - Skin Sens. 1, H317	-
Index No: 607-130-00-2 CAS No: 123-92-2 EC No: 204-662-3 Registration No: 01-2119548408-32-XXXX	[1] isopentyl acetate	0 - 2.5 %	Flam. Liq. 3, H226	-
Index No: 601-021-00-3 CAS No: 108-88-3 EC No: 203-625-9 Registration No: 01-2119471310-51-XXXX	[1] toluene	0 - 3 %	Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Repr. 2, H361d *** - Skin Irrit. 2, H315 - STOT RE 2 *, H373 ** - STOT SE 3, H336	-

(*): The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*, **, *** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 4 of 15

Print date: 12/07/2021

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 5 of 15

Print date: 12/07/2021

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not apply

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
ethanol, ethyl alcohol	64-17-5	United Kingdom [1]	Eight hours	1000	1920
			Short term		
		Éire [2]	Eight hours		
			Short term	1000	
		United States [3] (Cal/OSHA)	Eight hours	1000	
			Short term		
		United States [4] (NIOSH)	Eight hours	1000	
			Short term		
		United States [5] (OSHA)	Eight hours	1000	1900
			Short term		
(2-methoxymethylethoxy)propanol	34590-94-8	European Union [6]	Eight hours	50 (skin)	308 (skin)
			Short term		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021
Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 6 of 15
Print date: 12/07/2021

		United Kingdom [1]	Eight hours	50	308
			Short term		
		Éire [2]	Eight hours	50	308
			Short term		
		United States [3] (Cal/OSHA)	Eight hours	100	
			Short term	150	
		United States [4] (NIOSH)	Eight hours	100	
			Short term	150	
		United States [5] (OSHA)	Eight hours	100	600
			Short term		
Benzyl acetate	140-11-4	Éire [2]	Eight hours	10	
			Short term		
isopentyl acetate	123-92-2	European Union [6]	Eight hours	50	270
			Short term	100	540
		Éire [2]	Eight hours	50	260
			Short term	100	520
		United States [3] (Cal/OSHA)	Eight hours	50	
			Short term	100	
		United States [4] (NIOSH)	Eight hours	100	
			Short term		
United States [5] (OSHA)	Eight hours	100	525		
	Short term				
toluene	108-88-3	European Union [6]	Eight hours	50 (skin)	192 (skin)
			Short term	100 (skin)	384 (skin)
		United Kingdom [1]	Eight hours	50	191
			Short term	100	384
		Éire [2]	Eight hours	50	192
			Short term	100	384
		United States [3] (Cal/OSHA)	Eight hours	10	
			Short term	150 (Ceiling) 500	
		United States [4] (NIOSH)	Eight hours	100	
			Short term	150	
		United States [5] (OSHA)	Eight hours	200	
			Short term	300 Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift: 500 [10 min]	

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[6] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	DNEL (Workers)	Inhalation, Long-term, Systemic effects	950 (mg/m ³)
(R)-p-mentha-1,8-diene, d-limonene CAS No: 5989-27-5 EC No: 227-813-5	DNEL (Workers)	Inhalation, Long-term, Systemic effects	33,3 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Page 7 of 15

Version 2 (replaces version 1)

Revision date: 12/07/2021

Print date: 12/07/2021

Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	21,9 (mg/m ³)
Dihydromyrcenol (2,6-Dimethyloct-7-en-2-ol) CAS No: 18479-58-8 EC No: 242-362-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	73,5 (mg/m ³)
Geraniol CAS No: 106-24-1 EC No: 203-377-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	161,6 (mg/m ³)
Dodecanol (Alcohol C12) CAS No: 112-53-8 EC No: 203-982-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	35,3 (mg/m ³)
Linalyl acetate CAS No: 115-95-7 EC No: 204-116-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	2,75 (mg/m ³)
alpha-iso-Methylionone CAS No: 127-51-5 EC No: 204-846-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	29,4 (mg/m ³)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	20,8 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	5,1 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	2,95 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	1,47 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	1,47 (mg/kg bw/day)
toluene CAS No: 108-88-3 EC No: 203-625-9	DNEL (Workers)	Inhalation, Long-term, Local effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	192 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	56,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Systemic effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Systemic effects	226 (mg/m ³)
	DNEL (Workers)	Inhalation, Acute, Local effects	384 (mg/m ³)
	DNEL (General population)	Inhalation, Acute, Local effects	226 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	384 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	226 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	8,13 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
ethanol, ethyl alcohol	Fresh water	0,96 (mg/L)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 8 of 15

Print date: 12/07/2021

CAS No: 64-17-5 EC No: 200-578-6	Marine water	0,79 (mg/L)
	aqua (intermittent releases)	2,75 (mg/L)
	Soil	0,63 (mg/kg soil dw)
	sediment (freshwater)	3,6 (mg/kg sediment dw)
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	aqua (freshwater)	0,022 (mg/L)
	aqua (marine water)	0,022 (mg/L)
	aqua (intermittent releases)	0,22 (mg/L)
	STP	30 (mg/L)
	sediment (freshwater)	17,87 (mg/kg sediment dw)
	sediment (marine water)	1,787 (mg/kg sediment dw)
	soil	4,15 (mg/kg soil dw)
toluene CAS No: 108-88-3 EC No: 203-625-9	aqua (freshwater)	0,68 (mg/L)
	aqua (marine water)	0,68 (mg/L)
	aqua (intermittent releases)	0,68 (mg/L)
	STP	13,61 (mg/L)
	sediment (freshwater)	16,39 (mg/kg sediment dw)
	sediment (marine water)	16,39 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	air freshener		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	
Eye protection:			
PPE:	Face shield.		
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 9 of 15

Print date: 12/07/2021

CEN standards:	EN 165, EN 166, EN 167, EN 168	
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.	
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.	
Skin protection:		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: N.A./N.A.

Colour: Yellow

Odour: Characteristic

Odour threshold: N.A./N.A.

pH: 6 (100%)

Melting point: N.A./N.A.

Boiling Point: N.A./N.A.

Flash point: 17 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: N.A./N.A.

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 10 of 15

Print date: 12/07/2021

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
isopentyl acetate	Oral	LD50	Rabbit	7410 mg/kg bw [1]
	Dermal	LD50	Rabbit	>5000 mg/kg [1]
Inhalation		LOAEL	Cat	11600 mg/m ³ air [1]
	CAS No: 123-92-2 EC No: 204-662-3			[1] Ferdinand Flury und Wolfgang Wirth, International Archives of Occupational and Environmental Health Springer Berlin / Heidelberg ISSN 0340-0131 (Print), Heft Volume 5, Number 1, Seiten 1-90, Dezember 1933, DOI 10.1007/BF02274996

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 11 of 15

Print date: 12/07/2021

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	Fish	LC50	Leuciscus idus melanotus	36 mg/l (48 h) [1]
	Aquatic invertebrates	EC50	Daphnia magna Straus	205 mg/l (24 h) [1]
	Aquatic plants	ErC50	Desmodesmus subspicatus	>100 mg/l (48 h) [1]
toluene	Fish	LC50	Fish	31,7 mg/l (96 h) [1]
	Aquatic	LC50	Crustacean	92 mg/l (48 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 12 of 15

Print date: 12/07/2021

CAS No: 108-88-3 EC No: 203-625-9	invertebrates	[1] MacLean, M.M., and K.G. Doe 1989. The Comparative Toxicity of Crude and Refined Oils to Daphnia magna and Artemia. Environment Canada, EE-111, Dartmouth, Nova Scotia :64 p
	Aquatic plants	EC50 Algae 12,5 mg/l (72 h) [1] [1] Galassi, S., M. Mingazzini, L. Vigano, D. Cesareo, and M.L.Tosato 1988. Approaches to Modeling Toxic Responses of Aquatic Organisms to Aromatic Hydrocarbons. Ecotoxicol.Environ.Saf. 16(2):158-169

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethanol, ethyl alcohol CAS No: 64-17-5 EC No: 200-578-6	-0,3	-	-	Very low
(R)-p-mentha-1,8-diene, d-limonene CAS No: 5989-27-5 EC No: 227-813-5	4,83	-	-	High
Benzyl acetate CAS No: 140-11-4 EC No: 205-399-7	1,96	-	-	Very low
Geraniol CAS No: 106-24-1 EC No: 203-377-1	3,56	-	-	Moderate
Dodecanol (Alcohol C12) CAS No: 112-53-8 EC No: 203-982-0	5,13	-	-	Very high
Linalyl acetate CAS No: 115-95-7 EC No: 204-116-4	3,93	-	-	Moderate
isopentyl acetate CAS No: 123-92-2 EC No: 204-662-3	2,26	-	21,5 mg/L	Low
toluene CAS No: 108-88-3 EC No: 203-625-9	2,73	-	-	Low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021
Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 13 of 15
Print date: 12/07/2021

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number.

UN No: UN1993

14.2 UN proper shipping name.

Description:

ADR: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / (R)-P-MENTHA-1,8-DIENE D-LIMONENE), 3, PG II, (D/E)

IMDG: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / (R)-P-MENTHA-1,8-DIENE D-LIMONENE), 3, PG II

ICAO/IATA: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL ETHYL ALCOHOL / (R)-P-MENTHA-1,8-DIENE D-LIMONENE), 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.


Marine pollutant: No

14.6 Special precautions for user.

ADR LQ: 1 L

IMDG LQ: 1 L

ICAO LQ: 1 L



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S – Spills): F-E,S-E

Proceed in accordance with point 6.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 14 of 15

Print date: 12/07/2021

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 86,801 %

VOC content: 741,354 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
48. Toluene CAS No 108-88-3 EC No 203-625-9	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Kind of pollutant to water (Germany): WGK 2: Hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

049706-AMBIENTADOR MIKADO TIGER MISTERY 100ML LA CASA DE LOS AROMAS



JESÚS GÓMEZ, S.L.

Version 1 Date of compilation: 12/07/2021

Version 2 (replaces version 1)

Revision date: 12/07/2021

Page 15 of 15

Print date: 12/07/2021

Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Repr. 2 : Reproductive toxicant, Category 2
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AwSV: Facility Regulations for handling substances that are hazardous for the water.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.