


| | | | | | |
|----|--|---|---|--|--|
| 1 | General information | Supplier's name or trade mark | LEXMAN | | |
| 2 | | Supplier's address | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN | | |
| 3 | | Model Identifier - Luminaire Supplier reference | GU10-25P7.1W40 | | |
| 4 | | Light sources maker model | GU10-25P7.1W40 | | |
| 5 | | Date of placement on the market | 17/09/2022 | | |
| 6 | Type of light source: | Lighting technology used: | LED | | |
| 7 | | Light source cap type (or other electric interface) | GU10 | | |
| 8 | | Non-directional (NDLS) or directional (DLS): | DLS | | |
| 9 | | Mains (MLS) or non-mains (NMLS): | MLS | | |
| 10 | | Connected light source (CLS): | no | | |
| 11 | | Colour-tuneable light source: | no | | |
| 12 | | Envelope: | no | | |
| 13 | | High luminance light source: | no | | |
| 14 | | Anti-glare shield: | no | | |
| 15 | | Dimmable: | no | | |
| 16 | General product parameters: | Energy consumption in on-mode (kWh/1000 h) | 8 | kWh/1000h | |
| 17 | | Energy efficiency class | E | | |
| 18 | | Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm | 670 | 120 | |
| 19 | | Correlated colour type | single value | | |
| 20 | | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4000 | K | |
| 21 | | On-mode power (P_{on}), expressed in W and rounded to the first decimal | 7.1 | W | |
| 22 | | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0.00 | W | |
| 23 | | Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | 0.00 | W | |
| 24 | | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | | |
| 25 | | Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre) | | | |
| 26 | | Height (mm) | 53.00 | mm | |
| 27 | | Width (mm) | 50.00 | mm | |
| 28 | | Depth (mm) | 50.00 | mm | |
| 29 | | Parameters for LED and OLED light sources: | Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)) |  | |
| 30 | Claim of equivalent power | | yes | | |
| 31 | If yes, equivalent power (W) | | 65 | W | |
| 32 | Chromaticity coordinates (x and y) | | 0.382; 0.380 | | |
| 33 | Parameters for directional light sources: | Peak luminous intensity (cd) | 340 | cd | |
| 34 | | Beam angle in degrees (no decimal), or the range of beam angles that can be set | 100 | Degrees | |
| 35 | Parameter for LED and OLED light sources: | R9 colour rendering index value | 0 | | |
| 36 | | Survival factor rounded to the second decimal (>0.xx) | 0.90 | | |
| 37 | | Lumen maintenance factor rounded to the second decimal (>0.xx) | 0.96 | | |
| 38 | Parameters for LED and OLED mains lights sources: | displacement factor (cos ϕ_1) rounded to the second decimal | 0.92 | | |
| 39 | | Colour consistency in McAdam ellipses | 5.00 | | |
| 40 | | Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | - | | |
| 41 | | If yes then replacement claim (W) (no decimal) | | | |
| 42 | | Flicker metric (Pst LM) rounded to the first decimal | 0.3 | | |
| 43 | | Stroboscopic effect metric (SVM) rounded to the first decimal | 0.3 | | |
| 44 | Technical documentation name (in case of light source product) | GU10-25P7.1W40-Technical documentation for light source.pdf | | | |
| 45 | Light source removing instruction name (in case of containing product) | | | | |

| | | | | |
|----|---------|---|---|--------------------|
| 1 | (a) | Supplier's name and address | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN | |
| 2 | (b) | Model Identifier | GU10-25P7.1W40 | |
| 3 | (c) | Model identifier of all equivalent models already placed on the market | | |
| 4 | (d) | Identification and signature of the person empowered to bind the supplier | Refer to EU Declaration of Conformity | |
| 5 | (e) | Declared and measured values for the following technical parameters: | | |
| 6 | (e)(1) | <i>useful luminous flux (Φ_{use}) in lm</i> | 670 | Lm |
| 7 | (e)(2) | <i>colour rendering index (CRI)</i> | 80 | |
| 8 | (e)(3) | <i>on-mode power (P_{on}) in W</i> | 7.1 | W |
| 9 | (e)(4) | <i>beam angle in degrees for directional light sources (DLS)</i> | 100 | Degrees |
| 10 | (e)(5) | <i>correlated colour temperature (CCT) in K for FL and HID light sources</i> | 4000 | K |
| 11 | (e)(6) | <i>'standby power (P_{sb}) in W, including when it is zero</i> | 0.00 | W |
| 12 | (e)(7) | <i>networked standby power (P_{net}) in W for connected light sources (CLS) including when it is zero</i> | 0.00 | W |
| 13 | (e)(8) | <i>displacement factor ($\cos \phi_1$) for LED and OLED mains light sources</i> | 0.92 | |
| 14 | (e)(9) | <i>colour consistency in MacAdam ellipse steps for LED and OLED light sources</i> | 5 | |
| 15 | (e)(10) | <i>luminance-HLLS in cd/mm² (only for HLLS)</i> | NA | cd/mm ² |
| 16 | (e)(11) | <i>flicker metric (P_{stLM}) for LED and OLED light sources (rounded to one decimal)</i> | 0.3 | |
| 17 | (e)(12) | <i>stroboscopic effect metric (SVM) for LED and OLED light sources (rounded to one decimal)</i> | 0.3 | |
| 19 | (e)(13) | <i>excitation purity</i> | NA | |
| 20 | (f) | Calculations performed with the parameters, including the determination of the energy efficiency class | 670lm/7.1w*1.176=111lm/w, E class | |
| 21 | (g) | References to the harmonised standards applied or other standards used | EN 13032-1 :2004+A1:2012 EN 13032-4:2015+A1:2019 EN 62612:2013+A1:2017+A11:2017+A2:2018 IEC TR 61547-1:2020 IEC TR 63158:2018 | |
| 22 | (h) | Testing conditions if not described sufficiently in previous harmonised standards | NA | |
| 23 | (i) | the reference control settings, and instructions on how they can be implemented, where applicable | NA | |
| 24 | (j) | instructions on how to remove lighting control parts and/or non-lighting parts, if any, or how to switch them off or minimise their power consumption during light source testing | NA | |
| 25 | (k) | specific precautions that shall be taken when the model is assembled, installed, maintained or tested | NA | |