

## SOLID PIASTRELLA



DESCRIPTION	
Modular tile for outdoor flooring, easy to install and remove thanks to the click system	

MEASURES	
Dimensions	40 x 40 cm (1 mq = 3,2 pcs)
Thickness	3,3 cm

TECHNICAL DATA		
	TEST	VALUE
Loading Capacity	Pontarolo Engineering	26.000 kg/mq
Thermal expansion coefficient at 20°C	Pontarolo Engineering	0,05-0,1 mm/m° C
Material	Reg. CE n. 1907/2006	HDPE REACH* Assenza di sostanze SVHC

\*The result complies: determination of Flame Retardants Hexabromocyclododecane (HBCDD) and Polybromobiphenyls (PBB), determination of Flame Retardants Diphenyl ether, decabromo derivative (DecaBDE) and Diphenyl ether, octabromo derivative (OBDPE), determination of Chlorinated ParaFlines, determination of Cadmium content, content of Polycyclic Aromatic Hydrocarbons (PAH), content of certain Phthalates, determination of lead content, Polybrominated biphenyls (PBB) and Polybrominated diphenyl ethers (PBDE), content (including Deca-BD)

BENEFITS
Easy to install and remove thanks to the hooking system
Big size (less pieces per sqm)
Anti-slip
The surface can be completed with ramps and edges
Eco-friendly product (made of 100% recycled and recyclable materials)