## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MDC, SA

Supplier's address: SPV, P. Font del Ferro 55, 17403 Sant Hilari Sacalm Girona, ES

Model identifier: 52427-7

Type of light sou	ırce:	:
-------------------	-------	---

trol gear, light-

control

ing

Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		PCB CONNECTOR				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		Yes	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
	mption in on- 00 h), rounded st integer	7	Energy efficiency class	F		
Useful luminous flux (фuse), in-		801 in	Correlated colour	3 000 or 3		
dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		Sphere (360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	750 or 4 500		
On-mode power (P <sub>on</sub> ), ex- pressed in W		7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84		
Outer dimen-	Height	6	Spectral power dis-	See image		
sions without	Width	160	tribution in the	in last page		
separate con-	Depth	35	range 250 nm to 800			

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,400			
		nates (x and y)	0,385			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	15	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;