

1. Unique identification code of the product-type: **Corrugated bitumen sheets**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR: **corrugated bitumen sheets category S 3**. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Discontinuously laid roof coverings for buildings**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **ONDULINE FRANCE –Rue du Bac- BP15 – 76480 YAINVILLE – FRANCE – Tel 00 02 35 05 90 90 – Fax 00 02 35 05 91 11– email : info@onduline.fr**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard : **Not applicable**
8. Declared performance

| Essential characteristics                   | Performance                       | Harmonized technical specification |
|---|-----------------------------------|------------------------------------|
| Bending under downward load                 | Category S : >700N/m <sup>2</sup> | EN 534 (2010)                      |
| Impact strength                             | Category S : 250 mm               |                                    |
| Tearing strength                            | Category S: > 150 N               |                                    |
| Water permeability                          | Pass                              |                                    |
| Tearing strength after freeze/thaw ageing   | Category S: > 150 N               |                                    |
| Water permeability after freeze/thaw ageing | Pass                              |                                    |
| Thermal coefficient                         | $\alpha < 100 \times 10^{-6} 1/K$ |                                    |
| Reaction to Fire                            | E                                 |                                    |
| External fire performance                   | F                                 |                                    |
| Dangerous substances                        | NPD                               |                                    |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**DUBUC PASCAL Executive Director**

**Yainville, 01st of July 2013**

