## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	EGLO
--------------------------------	------

Supplier's address: EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

Model identifier: 2835-L500-120-9.7W-2700K-6500K

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Product parameters					
Anti-glare shield:	No	Dimmable:	No		
High luminance light source:	No				
Colour-tuneable light source:	No	Envelope:	-		
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
(or other electric interface)					
Light source cap-type	-				
5 5		directional:			
Lighting technology used:	LED	Non-directional or	NDLS		

## **Product parameters**

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
_ ·	mption in on- 00 h), rounded st integer	10	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 170 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500		
On-mode power (P <sub>on</sub> ), expressed in W		9,7	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	-	Spectral power dis-	See image		
sions without	Width	8	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	500	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	81	
		Chromaticity coordi-	0,462	
		nates (x and y)	0,419	
Parameters for LED and OLED light sources:				
R9 colour rendering index value 7		Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

