



Note:

- 1、 SST will be checked by assembled products. And the spec will follow with what quality specification mentioned:"24 hours of neutral salt spray test(NSS), Ra/Rp 7 (max 0,5% of the surface rusted) as per ISO10289;1999
- 2、 Load capacity: 30KG
- 3、 Breaking load:60KG
- 4、 Guarantee distance 5km at nominal load on smooth floor at less 2km/h speed
- 5、 Total weight:2.65KG
- 6、 Wheel clearance;lateral ± 2.5 mm, Angle $\pm 0.5^\circ$

11	Bolts	M6 x 25	2	6	12
10	Shaft card	$\phi 8$	2	2	4
9	Wheel	PP/TPR	2	90	180
8	Foot plate	Q195 $\phi 16 \times 1$	1	950	950
7	Bolts	M6 x 40	2	10	20
6	Washers	PVC	2	2	4
5	Nylon lock nut	M6	4	3	12
4	Down tube	Q195 $\phi 16 \times 1$	1	1025	1025
3	Locating rod	Q195	1	90	90
2	Up tube	Q195 $\phi 16 \times 1$	1	350	350
1	Handle foam	EVA $\phi 13 \times 100$	1	12	12
NO.	Name	material	Qty	Unit weight	Total weight (g)

Matrix code	TR01		EAN CODE				
Product designation	FOLDABLE HANDTRUCK 30KG STEEL STANDERS						
>0.5~3	>3~6	>6~30	>30~120	>120~400	>400~1000	>1000~2000	>2000~4000
± 0.1	± 0.2	± 0.3	± 0.5	± 1	± 3	± 5	± 8

Rev	NAME	DATE
01	陈俊华	2021.3.10
02		
03		
04		
05		
06		

adeo

AEDE 435, rue Sadi Carnot
CS 00001 - 59790 RONCHIN
FRANCE

MATERIAL/FINISHING:

GENERAL TOLERANCES: GB/T1804-m
LINEAR:
ANGULAR:

TITRE: Explosion Diagram

No. DE PLAN: GZS30ST-L

REVISION: A3

FEUILLE 1 SUR 1

ECHELLE: 1:6 (Scale can be adapted) Dimensions in mm