

No.	Name of Parts	Specifications	Unit	Qty	Remark
1	G21219 lamp shade	light diffusion PC (CM4272-DH) Tongyuan	PC	1	
2	G21219(60) lamp body	ADC 12	PC	1	One side spray coating, spray coating area 700cm²
3	BT2.9*6 Cross recessed pan head tapping screws (no slotted at)	Iron galvanizing (24h Salt spray test)	PC	4	2pcs PCB plates 2pcs driver
4	G21219-FGL-DB PCB plate		PC	1	
5	VED single core wire (red) L=110MM (one end is stripped with 3mm wire and soaked in tin with a 2.5 * 30mm heat shrink sleeve, and one end is covered with copper head)	H05V-K 1x0.5mm²	PC	1	
6	VED single core wire (black) L=110MM (one end stripped with 3mm wire and soaked in tin with a	H05V-K 1x0.5mm²	PC	1	
7	G21219(60)panel bracket	ABS 417 black	PC	1	
8	PA8 Two hole terminal without letters		PC	1	
9	G21209-FGL-QD input VDE dual core wire L=450MM stripped wire 9mm and tin immersed output red black wire L=80MM copper clad		PC	1	
10	BT2.9*8 Cross recessed pan head tapping screws (no slotted at)	Iron galvanizing (24h Salt spray test)	PC	4	
11	40 tube PA8 junction box crimping board	PA6+GF30 black	PC	2	
12	M4*8 Cross shaped pan head self extrusion screw	hardness 450HV0.3, zinc surface-plating	PC	1	
13	φ4 Serrated lock washers external teeth	zinc surface-plating	PC	2	
14	Yellow green grounding wire (Φ4) L=450MM (with lettering) wire stripping 9mm and tin dipping	H05V-K 1*0.75MM²	PC	1	
15	M4*10 Eleven slot pan head screw	Iron galvanizing	PC	2	
16	G21219(60) section bar	6063	PC	1	One side spray coating, spray
17	G21219(60) base	ADC12	PC	1	One side spray coating, spray
18	M4*10 Cross recessed countersunk head screws (head Φ6.5)	stainless steel 304, black zinc plating on surface	PC	2	
19	Ø14 Two hole protective coil (SW)	silicone 50° black	PC	1	
20	Rubber cover for junction box	silicone 50° black	PC	1	
21	PA10-10-3 bilateral pressing terminal		PC	1	
22	Rubber cover for junction box	PA6+GF30 black	PC	1	
23	Small protective coil	silicone 50° black	PC	1	
24	Crimping buckle up (φ4 hole)	PC110U black	PC	1	
25	ST2.9*10 Cross recessed pan head tapping screws	zinc surface-plating	PC	2	
26	M4*10 Cross recessed countersunk head screws (head Φ6.5)	stainless steel 304, black zinc plating on surface	PC	2	as attachment
27	ST4.2*40 Cross recessed flat round head tapping screws	stainless steel 304	PC	2	as attachment
28	φ6*30 Plastic expansion	φ6, HDPE	PC	2	as attachment
29	Leibang 6016HT	310ML/bottle	PC	0.007	
30	RTV glue		PC	0.001	

