


|    |  |  |   |           |   |
|----|--|--|---|-----------|---|
| 1  | General information  | Supplier's name or trade mark  | INSPIRE   |           |   |
| 2  |  | Supplier's address   | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN   |           |   |
| 3  |  | Model Identifier - Luminaire Supplier reference  | 2128SW-1.5M   |           |   |
| 4  |  | Light sources maker model  | 2128SW-DB   |           |   |
| 5  |  | Date of placement on the market  | 01/2024   |           |   |
| 6  | Type of light source:  | Lighting technology used:  | LED   |           |   |
| 7  |  | Light source cap type (or other electric interface)  | Connector   |           |   |
| 8  |  | Non-directional (NDLS) or directional (DLS):   | NDLS  |           |   |
| 9  |  | Mains (MLS) or non-mains (NMLS):   | NMLS  |           |   |
| 10 |  | Connected light source (CLS):  | no  |           |   |
| 11 |  | Colour-tuneable light source:  | no  |           |   |
| 12 |  | Envelope:  | no  |           |   |
| 13 |  | High luminance light source:   | no  |           |   |
| 14 |  | Anti-glare shield:   | no  |           |   |
| 15 |  | Dimmable:  | no  |           |   |
| 16 | General product parameters:  | Energy consumption in on-mode (kWh/1000 h)   | 1   | kWh/1000h |   |
| 17 |  | Energy efficiency class  | D   |           |   |
| 18 |  | <b>Useful luminous flux (<math>\Phi_{use}</math>)</b> , indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm | 200   | 360       |   |
| 19 |  | Correlated colour type   | single value  |           |   |
| 20 |  | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set                       | 4000  | K         |   |
| 21 |  | On-mode power ( $P_{on}$ ), expressed in W and rounded to the first decimal  | 1.4   | W         |   |
| 22 |  | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0.00  | W         |   |
| 23 |  | Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | 0.00  | W         |   |
| 24 |  | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80  |           |   |
| 25 |  | Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)  |   |           |   |
| 26 |  | Height (mm)  | 500.00  | mm        |   |
| 27 |  | Width (mm)   | 8.00  | mm        |   |
| 28 |  | Depth (mm)   | 0.95  | mm        |   |
| 29 |  | Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg))                  | 2128SW-1.5M_Spectral power distribution.pdf  |           |   |
| 30 |  | Claim of equivalent power  | -   |           |   |
| 31 | If yes, equivalent power (W)   |  |   | W         |   |
| 32 | Chromaticity coordinates (x and y)                                     | 0.380;0.380  |   |           |   |
| 33 | Parameters for directional light sources:                              | Peak luminous intensity (cd)   |   |           |   |
| 34 |  | Beam angle in degrees (no decimal), or the range of beam angles that can be set  |   |           |   |
| 35 | Parameters for LED and OLED light sources:                             | R9 colour rendering index value  | 3   |           |   |
| 36 |  | Survival factor rounded to the second decimal (>0.xx)  | 0.90  |           |   |
| 37 |  | Lumen maintenance factor rounded to the second decimal (>0.xx)   | 0.96  |           |   |
| 38 | Parameters for LED and OLED mains lights sources:                      | displacement factor (cos $\phi_1$ ) rounded to the second decimal  | 0.000   |           |   |
| 39 |  | Colour consistency in McAdam ellipses  | 6.0   |           |   |
| 40 |  | Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.  | -   |           |   |
| 41 |  | If yes then replacement claim (W) (no decimal)   |   |           | W |
| 42 |  | Flicker metric (Pst LM) rounded to the first decimal   | 0.000   |           |   |
| 43 | Stroboscopic effect metric (SVM) rounded to the first decimal          | 0.000  |   |           |   |
| 44 | Technical documentation name (in case of light source product)         |  |   |           |   |
| 45 | Light source removing instruction name (in case of containing product) |  | 2128SW-1.5M_Light source removing instruction.pdf   |           |   |