


1	General information	Supplier's name or trade mark	SENSEA	
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN	
3		Model Identifier - Luminaire Supplier reference	MF10S08SL-MB (2024R07P04-0038)	
4		Light sources maker model	REMIX	
5		Date of placement on the market		
6	Type of light source:	Lighting technology used:	LED	
7		Light source cap type (or other electric interface)	No cap-type	
8		Non-directional (NDLS) or directional (DLS):	NDLS	
9		Mains (MLS) or non-mains (NMLS):	NMLS	
10		Connected light source (CLS):	no	
11		Colour-tuneable light source:	no	
12		Envelope:	no	
13		High luminance light source:	no	
14		Anti-glare shield:	no	
15		Dimmable:	no	
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h)	27	kWh/1000h
17		Energy efficiency class	D	
18		Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm	4108	
19		Correlated colour type	single value	
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, expressed in K	3000 - 6000	K
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal	26.5	W
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal		W
23		Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		W
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)		
26		Height (mm)	8.00	mm
27		Width (mm)	2200.00	mm
28		Depth (mm)	1.00	mm
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)		
30	Claim of equivalent power			
31	If yes, equivalent power (W)		W	
32	Chromaticity coordinates (x and y)			
33	Parameters for directional light sources:	Peak luminous intensity (cd)		cd
34		Beam angle in degrees (no decimal), or the range of beam angles that can be set		Degrees
35		R9 colour rendering index value	28	
36	Parameter for LED and OLED light sources:	Survival factor rounded to the second decimal ($>0.xx$)		
37		Lumen maintenance factor rounded to the second decimal ($>0.xx$)		
38	Parameters for LED and OLED mains lights sources:	displacement factor ($\cos \phi_1$) rounded to the second decimal		
39		Colour consistency in McAdam ellipses	6.0	
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		
41		If yes then replacement claim (W) (no decimal)		W
42		Flicker metric (Pst LM) rounded to the first decimal		
43	Stroboscopic effect metric (SVM) rounded to the first decimal			
44	Technical documentation name (in case of light source product)			
45	Light source removing instruction name (in case of containing product)			