

Group BII_a
Annex J
0012a20130701



ROIG CERÁMICA S.A.

Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

05

0012a20130701

EN 14411

Dry-pressed ceramic tiles and tile pieces, with a water absorption rate of $3\% < E_b \leq 6\%$, for use on indoor walls and floors.

Reaction to fire	A1 _{FL} /A1
Breaking strength	> 1000 N
Adhesion/bonding strength for: C1-rated cement-based adhesive	> 0.5 N/mm ²
Durability for: Indoor use	Complies

Group BIII
Annex L
001b320130701



ROIG CERÁMICA S.A.

Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

05

001b320130701

EN 14411

Dry-pressed ceramic tiles and tile pieces, with a water absorption rate of $E_b > 10\%$, for use on indoor walls.

Reaction to fire	A1
Adhesion/bonding strength for: C1-rated cement-based adhesive	> 0.5 N/mm ²
Durability for: Indoor use	Complies

Group BI_b
Annex H
0011b20130701



ROIG CERÁMICA S.A.

Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

05

0011b20130701

EN 14411

Dry-pressed ceramic tiles and tile pieces, with a water absorption rate of $0.5\% < E_b \leq 3\%$, for use on indoor walls and floors.

Reaction to fire	A1 _{FL} /A1
Breaking strength	> 1100 N
Adhesion/bonding strength for: C2-rated cement-based adhesive	> 1 N/mm ²
Durability for: Indoor use	Complies

Group BI_a
Annex G
0011a20130701



ROIG CERÁMICA S.A.

Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

05

0011a20130701

EN 14411

Dry-dressed ceramic tiles and tile pieces, with a water absorption rate of $E_b \leq 0.5\%$, for indoor and outdoor walls and floors.

Reaction to fire	A1 _{FL} /A1
Breaking strength	> 1300 N
Adhesion/bonding strength for: C2-rated cement-based adhesive	> 1 N/mm ²
Thermal shock resistance	Complies
Durability for: Indoor use	Complies
Outdoor use: freeze thaw resistance	Complies

Group BI_a
Annex G
0011a20130701v



ROIG CERÁMICA S.A.

Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

05

0011a20130701v

EN 14411

Dry-pressed ceramic tiles and tile pieces, with a water absorption rate of $E_b \leq 0.5\%$, for indoor and outdoor walls and floors.

Reaction to fire	A1 _{FL} /A1
Breaking strength	> 700 N
Adhesion/bonding strength for: C2-rated cement-based adhesive	> 1 N/mm ²
Thermal shock resistance	Complies
Durability for: Indoor use	Complies
Outdoor use: freeze thaw resistance	Complies

DECLARATION OF PERFORMANCE

No. 0012a20130701

1. **Unique identification of product type (type, batch or serial number or any other element allowing for the identification of the product):**

Ceramic tiles and tile pieces with a water absorption rate of $3\% < E_b \leq 6\%$

2. **Intended use(s):** Indoor walls and floors.

3. **Name or registered trademark and contact address of manufacturer:**

ROIG CERÁMICA S.A.
Camino Foyes Ferraes, 15
12110 L'Alcora (Castellón)
España – Spain

4. **System of assessment and verification of constancy of performance:**

System 4

5. **Name and identification number of notified laboratory, if relevant. Tasks carried out, system of assessment, issued document and issue date:**

Not applicable

6. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2016
Breaking strength	> 1000 N	
Adhesion/bonding strength <i>C1-rate cement-based adhesive</i>	> 0.5 N/mm ²	
Slip resistance	NPD	
Tactile properties	NPD	
Release of dangerous substances <i>Lead</i> <i>Cadmium</i>	NPD NPD	
Durability for: <i>Indoor use</i>	Complies	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer by:



Vicente Peris
Quality Manager

Alcora, on November 18, 2021

DECLARATION OF PERFORMANCE**No. 001b320130701**

1. **Unique identification of product type (type, batch or serial number or any other element allowing for the identification of the product):**

Ceramic tiles and tile pieces with a water absorption rate of $E_b > 10\%$

2. **Intended use(s):** Indoor walls.

3. **Name or registered trademark and contact address of manufacturer:**

ROIG CERÁMICA S.A.
Camino Foyes Ferraes, 15
12110 L'Alcora (Castellón)
España – Spain

4. **System of assessment and verification of constancy of performance:**

System 4

5. **Name and identification number of notified laboratory, if relevant. Tasks carried out, system of assessment, issued document and issue date:**

Not applicable

6. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1	EN 14411:2016
Release of dangerous substances <i>Cadmium emissions (Cd)</i> <i>Lead emissions (Pb)</i>	NPD NPD	
Adhesion/bonding strength <i>C1-rate cement-based adhesive</i>	> 0.5 N/mm ²	
Durability for: <i>Indoor use</i>	Complies	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer by:



Vicente Peris
Quality Manager

Alcora, on November 18, 2021

DECLARATION OF PERFORMANCE

No. 0011b20130701

1. **Unique identification of product type (type, batch or serial number or any other element allowing for the identification of the product):**

Dry-pressed ceramic tiles and tile pieces with a water absorption rate of $0.5\% < E_b \leq 3\%$

2. **Intended use(s):** Indoor walls and floors.

3. **Name or registered trademark and contact address of manufacturer:**

ROIG CERÁMICA S.A.
 Camino Foyes Ferraes, 15
 12110 L'Alcora (Castellón)
 España – Spain

4. **System of assessment and verification of constancy of performance:**

System 4

5. **Name and identification number of notified laboratory, if relevant. Tasks carried out, system of assessment, issued document and issue date:**

Not applicable

6. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2016
Breaking strength	> 1100 N	
Adhesion/bonding strength <i>C2-rate cement-based adhesive</i>	> 1 N/mm ²	
Slip resistance	NPD	
Tactile properties	NPD	
Release of dangerous substances <i>Lead</i> <i>Cadmium</i>	NPD NPD	
Durability for: <i>Indoor use</i>	Complies	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer by:



Vicente Peris
Quality Manager

Alcora, on November 18, 2021

DECLARATION OF PERFORMANCE**No. 0011a20130701**

1. **Unique identification of product type (type, batch or serial number or any other element allowing for the identification of the product):**

Ceramic tiles and tile pieces with a water absorption rate of $E_b \leq 0.5\%$

2. **Intended use(s):** Indoor and outdoor walls and floors.

3. **Name or registered trademark and contact address of manufacturer:**

ROIG CERÁMICA S.A.
Camino Foyes Ferraes, 15
12110 L'Alcora (Castellón)
España – Spain

4. **System of assessment and verification of constancy of performance:**

System 4

5. **Name and identification number of notified laboratory, if relevant. Tasks carried out, system of assessment, issued document and issue date:**

Not applicable

6. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2016
Breaking strength	> 1300 N	
Slip resistance	NPD	
Tactile properties	NPD	
Adhesion/bonding strength <i>C2-rate cement-based adhesive</i>	> 1 N/mm ²	
Thermal shock resistance	Complies	
Durability for: Indoor use Outdoor use: freeze thaw resistance	Complies Complies	
Release of dangerous substances <i>Lead</i> <i>Cadmium</i>	NPD NPD	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer by:



Vicente Peris
Quality Manager

Alcora, on November 18, 2021

DECLARATION OF PERFORMANCE

No. 0011a20130701v

1. **Unique identification of product type (type, batch or serial number or any other element allowing for the identification of the product):**

Ceramic tiles and tile pieces with a water absorption rate of $E_b \leq 0.5\%$

2. **Intended use(s):** Indoor and outdoor walls and floors.

3. **Name or registered trademark and contact address of manufacturer:**

ROIG CERÁMICA S.A.
Camino Foyes Ferraes, 15
12110 L'Alcora (Castellón)
España – Spain

4. **System of assessment and verification of constancy of performance:**

System 4

5. **Name and identification number of notified laboratory, if relevant. Tasks carried out, system of assessment, issued document and issue date:**

Not applicable

6. **Declared performance:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1 _{FL} /A1	EN 14411:2016
Breaking strength	> 700 N	
Slip resistance	NPD	
Tactile properties	NPD	
Adhesion/bonding strength <i>C2-rate cement-based adhesive</i>	> 1 N/mm ²	
Thermal shock resistance	Complies	
Durability for: Indoor use Outdoor use: freeze thaw resistance	Complies Complies	
Release of dangerous substances <i>Lead</i> <i>Cadmium</i>	NPD NPD	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed on behalf of the manufacturer by:



Vicente Peris
Quality Manager

Alcora, on November 18, 2021