

Manufacturer	
Outdoor unit	
Indoor unit	



ARXM35A5V1B

ATXM35A5V1B

Outdoor sound power level (dB)	dB(A)	58.0
Indoor sound level	dB(A)	58.0
The refrigerant (GWP)		R-32 (675)

Cooling mode

SEER		9.10
Classe di efficienza energetica		A+++
Annual electricity consumption	kWh/a	135
Design load Pdesignc	kW	3.50

Heating mode: Average climate

Design temperature = -10°C

SCOP		5.15
Classe di efficienza energetica		A+++
Annual electricity consumption	kWh/a	679
Design load Pdesignh at -10°C	kW	2.50
Required back up heating capacity at -10°C	kW	0.00
Declared capacity at -10°C	kW	2.5

Heating mode: Warm climate

Design temperature = 2°C

SCOP		6.33
Classe di efficienza energetica		A+++
Annual electricity consumption	kWh/a	312
Design load Pdesignh at 2°C	kW	1.41
Required back up heating capacity at 2°C	kW	0.00
Declared capacity at 2°C	kW	1.41

Heating mode: Cold climate

Design temperature = -22°C

SCOP		
Classe di efficienza energetica		
Annual electricity consumption	kWh/a	
Design load Pdesignh at -22°C	kW	
Required backup heating capacity at -22°C	kW	
Declared capacity at -22°C	kW	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Consumo di energia in base ai risultati della prova campione. Il consumo reale di energia è funzione della maniera in cui l'apparecchio viene utilizzato e della posizione in cui è collocato.