

Manufacturer	
Outdoor unit	
Indoor unit	



RXC35DV1B

FTXC35DV1B

Outdoor sound power level (dB)	dB(A)	60.0
Indoor sound level	dB(A)	58.0
The refrigerant (GWP)		R-32 (675.0)

Cooling mode

SEER		6.87
Classe di efficienza energetica		A++
Annual electricity consumption	kWh/a	175
Design load Pdesignc	kW	3.44

Heating mode: Average climate

Design temperature = -10°C

SCOP		4.28
Classe di efficienza energetica		A+
Annual electricity consumption	kWh/a	733
Design load Pdesignh at -10°C	kW	2.24
Required back up heating capacity at -10°C	kW	0.520
Declared capacity at -10°C	kW	1.72

Heating mode: Warm climate

Design temperature = 2°C

SCOP		5.69
Classe di efficienza energetica		A+++
Annual electricity consumption	kWh/a	507
Design load Pdesignh at 2°C	kW	2.06
Required back up heating capacity at 2°C	kW	0.00
Declared capacity at 2°C	kW	2.06

Heating mode: Cold climate

Design temperature = -22°C

SCOP		
Classe di efficienza energetica		
Annual electricity consumption	kWh/a	
Design load Pdesignh at -22°C	kW	
Required backup heating capacity at -22°C	kW	
Declared capacity at -22°C	kW	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675.0. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675.0 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Consumo di energia in base ai risultati della prova campione. Il consumo reale di energia è funzione della maniera in cui l'apparecchio viene utilizzato e della posizione in cui è collocato.