# DECLARATION OF PERFORMANCE No. BUA 3W 01/12/2018 / 109943-1

1. Unique product identification code:

BCB, BC2, BC1, BC4, BC8, BK1, BK2, BK4, BK8, BK9, BKT, BKW, BCC, BCA, BCU, BKU, BKA

2. Intended use or uses:

The three-layer floorboards are designed for installation in inside rooms. Suitable for installation on top of a hydronic or electric underfloor heating system. Suited to be installed as a floating floor or fixed to the subfloor. Pre-coated with varnish or oil and ready for use immediately after installation.

3. Supplier:

### MAS MADERA FLOORING GROUP S.L. C/TOPACIO 15 47012 VALLADOLID

4. Authorised representative: not applicable

5. System(s) for assessment and verification of constancy of performance: 3

6. Harmonised standard: EN 14342:2013

EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Zellescher Weg 24, 01217 Dresden, Germany,

Notification number: 0766

performed type examination according to system 3 and issued type examination reports.

7. Declared performance:

Essential features	Performance	Harmonised technical specifications
Reaction to fire	Dfl - s1	EN 14342:2013
Minimum density	500 kg/m3	
Minimum thickness	10 mm	
Formaldehyde emissions	E-1	
Pentachlorophenol emissions	NPD	
Thermal conductivity	0.14 W/mK	
Slip	NPD	
Biological stability	NPD	

## 8. Relevant or special technical documentation: Product technical specifications

The performance of the above-described product corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the said manufacturer.

Signed on behalf of the supplier:

Salvador Mieres Panedas, Manager

(name and title)

Valladolid, March 15, 2023 (place and date of issue)

(signature)

# DECLARATION OF PERFORMANCE No. BUA 3W 01/12/2018 / 109943-2

#### 1. Unique product identification code:

#### BLC

#### 2. Intended use or uses:

The three-layer floorboards are designed for installation in inside rooms. Suitable for installation on top of a hydronic or electric underfloor heating system. Suited to be installed as a floating floor or fixed to the subfloor. Pre-coated with varnish or oil and ready for use immediately after installation.

### 3. Supplier:

### MAS MADERA FLOORING GROUP S.L. C/TOPACIO 15 47012 VALLADOLID

4. Authorised representative: not applicable

5. System(s) for assessment and verification of constancy of performance: 3

6. Harmonised standard: EN 14342:2013

EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Zellescher Weg 24, 01217 Dresden, Germany,

Notification number: 0766

performed type examination according to system 3 and issued type examination reports.

7. Declared performance:

Essential features	Performance	Harmonised technical specifications
Reaction to fire	Dfl - s1	EN 14342:2013
Minimum density	500 kg/m3	
Minimum thickness	10 mm	
Formaldehyde emissions	E-1	
Pentachlorophenol emissions	NPD	
Thermal conductivity	0.14 W/mK	
Slip	NPD	
Biological stability	NPD	

# 8. Relevant or special technical documentation: Product technical specifications

The performance of the above-described product corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the said manufacturer.

Signed on behalf of the supplier:

Salvador Mieres Panedas, Manager (name and title)

(signature

Valladolid, March 15, 2023 (place and date of issue)

# DECLARATION OF PERFORMANCE No. BUA 3W 01/12/2018 / 109943-3

1. Unique product identification code:

#### BVU

#### 2. Intended use or uses:

The three-layer floorboards are designed for installation in inside rooms. Suitable for installation on top of a hydronic or electric underfloor heating system. Suited to be installed as a floating floor or fixed to the subfloor. Pre-coated with varnish or oil and ready for use immediately after installation.

3. Supplier:

### MAS MADERA FLOORING GROUP S.L. C/ TOPACIO 15 47012 VALLADOLID

4. Authorised representative: not applicable

5. System(s) for assessment and verification of constancy of performance: 3

6. Harmonised standard: EN 14342:2013

EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Zellescher Weg 24, 01217 Dresden, Germany,

Notification number: 0766

performed type examination according to system 3 and issued type examination reports.

7. Declared performance:

Essential features	Performance	Harmonised technical specifications
Reaction to fire	Dfl - s1	EN 14342:2013
Minimum density	500 kg/m3	
Minimum thickness	10 mm	
Formaldehyde emissions	E-1	
Pentachlorophenol emissions	NPD	
Thermal conductivity	0.14 W/mK	
Slip	NPD	
Biological stability	NPD	

# 8. Relevant or special technical documentation: Product technical specifications

The performance of the above-described product corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the said manufacturer.

Signed on behalf of the supplier:

Salvador Mieres Panedas, Manager (name and title)

Valladolid, March 15, 2023 (place and date of issue)

(signature