



Light Source Technical DataSheet

EAN	3276007366518
Product Supplier reference	G18082P(56)WH
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	INSPIRE
Replaceability of Light source	by qualified person
Light sources maker model	G18082-FGL-MZ-2835-D
Link to EU Product Data base	https://eprel.ec.europa.eu/screen/product/lightsources/0
Spectral power distribution in the range 250 nm to 800 nm. at full-load	<p>The graph shows the relative power distribution of the light source. The y-axis is labeled '相对光谱' (Relative Spectrum) and ranges from 0.0 to 1.2. The x-axis is labeled '波长 (nm)' (Wavelength (nm)) and ranges from 380 to 1000. The curve shows a sharp peak at approximately 450 nm (blue) and a broader peak at 675 nm (red). The text '1.0 = 3.666e+001lm/m' is visible in the top right corner of the graph area.</p>
If the light source contains mercury: instructions on how to clean up the debris in case of accidental breakage	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for advice on recycling.

