

DECLARATION OF PERFORMANCE

N°2-KDM15

1. Identification of the product: **Dry-pressed ceramic tiles, with water absorption $0,5 < E \leq 3$ % Blb**
2. Intended use: **for internal and external walls and floorings**
3. Name and contact of the manufacturer: **KERADOM SRL - - VIA BOTTICELLI 10 – 42048 RUBIERA(RE) ITALY**
4. System of assessment and verification of constancy of performance (AVCP): **System 3 and 4**
5. Notified laboratory: **Modena Centro Prove s.r.l. – Via Sallustio n° 78 Modena (MO) Italy. Identification number 1599**
6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1fl/A1	EN 14411:2012
Release of dangerous substances, for: - Cadmium - Lead	NPD	
Breaking strength (thickness > 7,5mm)	≥ 1100 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for: Cementitious adhesive, type C2	≥ 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for: -internal use: -external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.
 Signed for and behalf of the manufacturer by:

Giovanni Rinaldi / Amm.re Unico

Name and function

RUBIERA (RE) 09/06/2015

Place and date of the issue

Keradom srl

Signature