


DECLARATION OF PERFORMANCE

No: GGLS FFKF06 2076 26BM07

1. Unique identification code of the product type: GGLS FFKF06 2076 26BM07
2. Intended use/es: Communication in domestic and commercial locations
3. Manufacturer: VELUX A/S, Ådalsvej 99, DK-2970 Hørsholm, www.velux.com
5. Systems of assessment and verification of constancy of performance (AVCP): System 3
6. Harmonised standard: EN 14351-1:2006+A2:2016, Notified body/ies: 0757, 0757, 0845, 1235*
7. Declared performance:

Essential characteristics	Performance	§	NB*
Resistance to wind load	class C3 ¹	4.2	1235
Resistance to snow load	4 mm toughened glass - 16 mm - 6.8 mm laminated float glass	4.3	
Reaction to fire	class C-s1,d2	4.4.1	0402
External fire performance	NPD	4.4.2	
Watertightness	class 9A	4.5	1235
Impact resistance	class 3 ²	4.7	1235
Load-bearing capacity of safety devices	passed	4.8	1235
Acoustic performance	34(-1;-4)	4.11	0199, EN14351-1, table B.1/B.2
Thermal transmittance ³	1.4 W/(m²K)	4.12	1235
Solar factor	0.30	4.13	0757
Light transmittance	0.62	4.13	0757
Air permeability	class 4	4.14	1235
NPD: No performance determined, passed: test is passed * Notified body/ies: http://ec.europa.eu/growth/tools-databases/nando/ ¹ For window width > 1270 mm or window height > 1398 mm: NPD ² For window width > 550 mm or window height > 778 mm: NPD ³ For reference size 1.23 x 1.48 m + tolerances, 90° installation, In accordance with EN 10077-1/2			

The performance of the product identified above is in conformity with the set of declared performance/s.
 This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Klaus Lorentzen, Vice President
 Ådalsvej 99, DK 2970 – Hørsholm, 2021-06-28

CE 13		GGLS FFKF06 2076 26BM07 Communication in domestic and commercial locations		Harmonised standard: EN 14351-1:2006+A2:2016	
Essential characteristics		Performance		§	NB*
Resistance to wind load		class C3 ¹		4.2	1235
Resistance to snow load		4 mm toughened glass - 16 mm - 6.8 mm laminated float glass		4.3	
Reaction to fire		class C-s1,d2		4.4.1	0402
External fire performance		NPD		4.4.2	
Watertightness		class 9A		4.5	1235
Impact resistance		class 3 ²		4.7	1235
Load-bearing capacity of safety devices		passed		4.8	1235
Acoustic performance		34(-1;-4)		4.11	0199, EN14351-1, table B.1/B.2
Thermal transmittance ³		1.4 W/(m²K)		4.12	1235
Solar factor		0.30		4.13	0757
Light transmittance		0.62		4.13	0757
Air permeability		class 4		4.14	1235
NPD: No performance determined, passed: test is passed					
* Notified body/ies: http://ec.europa.eu/growth/tools-databases/nando/					
¹ For window width > 1270 mm or window height > 1398 mm: NPD					
² For window width > 550 mm or window height > 778 mm: NPD					
³ For reference size 1.23 x 1.48 m + tolerances, 90° installation, In accordance with EN 10077-1/2					

