



Main

| | |
|---------------------------|-------------------------------------|
| Range | Odace |
| Product or component type | Socket-outlet |
| Device presentation | Mechanism with plastic fixing frame |
| Socket number | 1 |
| Quantity per set | Set of 1 |
| Number of terminals | 2 |
| Condition of use | Indoor |

Complementary

| | |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device mounting | Flush |
| Outlet poles configuration | 2P with shutters |
| Outlet standard description | Without earthing contact |
| Fixing mode | Screws |
| Colour tint | Anthracite |
| Surface finish | Glossy |
| Rated current | 16 A at 250 V AC 50 Hz |
| Service life in cycles | 5000 Cycles |
| Electrical durability | 5000 Cycles |
| Connections - terminals | Screw terminals |
| Shape of screw head | Pozidriv No 1 |
| Clamping connection capacity | 1 x 1.5...2 x 4 mm ² for rigid cable(s) 1 x 1.5...2 x 4 mm ² for stranded cable(s) 1 x 1.5...2 x 4 mm ² for flexible cable(s) |
| Wire stripping length | 12 Mm |
| Material | ASA + PC: mechanism cover PBT (polybutylene terephthalate) GF30: support frame PC (polycarbonate) GF10 FR: casing |
| Height | 71 Mm |
| Width | 71 Mm |
| Depth | 42.5 Mm |
| Embedding depth | 26.5 Mm |
| Net weight | 0.041 Kg |

Environment

| | |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Ambient air temperature for storage | -5...50 °C |
| Dielectric strength | 2000 V |
| Ambient air temperature for operation | 5...35 °C |
| Standards | UNE 20315-1-1 UNE 20315-1-2 NF C 61-314 |
| Product certifications | AENOR: 030/2210 LCIE: NF 603415A NF |
| IK degree of protection | IK04 |
| IP degree of protection | IP21D |
| Environmental characteristic | Bleach Petrol Acetone Alcohol Liquid soap UV resistant Ammonia Oil Window-cleaning fluid |
| Environmental health and issues | Halogen free |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**