



### Main

Range	Odace
Product or component type	Switch
Device presentation	Mechanism with plastic fixing frame
Device application	Fan
Quantity per set	Set of 1
Condition of use	Indoor

### Complementary

Device mounting	Flush
Switch function	1-pole 2-way
Number of rocker	1
Actuator	Rocker
Fixing mode	By screws
Colour tint	Anthracite
Rated current	10 AX at 250 V AC 50/60 Hz
Load type	Load for energy saving lamps with ballast: 100 W
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un with $\cos \varphi = 0.3$
Service life in cycles	20000 Cycles at 5 In ON + In OFF 20000 Cycles at ON and OFF at rated voltage with $\cos \varphi = 0.6$
Electrical durability	20000 Cycles at ON and OFF at rated voltage with $\cos \varphi = 0.6$ 20000 Cycles at 5 In ON + In OFF
Number of terminals	3 screwless terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> for rigid cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for flexible cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for stranded cable(s)
Wire stripping length	12 Mm
Material	Thermoplastic ABS-UV stabilised: centre plate PBT (polybutylene terephthalate) GF30: support frame PC (polycarbonate) GF10 FR: casing
Height	71 Mm
Width	71 Mm
Depth	33.6 Mm
Embedding depth	18.75 Mm
Net weight	0.04 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	5...35 °C
Standards	2006/95/EEC EN 60669-1
Product certifications	AENOR: 030/2237 LCIE: NF 619318A NF
IK degree of protection	IK04
IP degree of protection	IP21D
Environmental characteristic	Petrol Bleach Acetone UV resistant Liquid soap Oil Alcohol Ammonia Window-cleaning fluid
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**