



Main

Range	Odace
Product or component type	Socket-outlet
Device presentation	Complete socket-outlet
Socket number	2
Quantity per set	Set of 1
Number of terminals	3
Condition of use	Indoor

Complementary

Device mounting	Semi flush
Outlet poles configuration	2P + E with shutters
Outlet standard description	Pin earth
Outlet standard	French
Fixing mode	Screws
Colour tint	White (RAL 9003)
Surface finish	Glossy
Rated current	16 A at 250 V AC 50 Hz
Service life in cycles	5000 Cycles
Electrical durability	5000 Cycles
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 4 mm ² for rigid cable(s) 1 x 1.5...2 x 4 mm ² for stranded cable(s) 1 x 1.5...2 x 4 mm ² for flexible cable(s)
Wire stripping length	12 Mm
Material	ASA + PC: mechanism cover PC (polycarbonate) GF10 FR: casing Sheet metal: support frame
Height	126 Mm
Width	85 Mm
Depth	46 Mm
Embedding depth	27.1 Mm
Net weight	0.111 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	5...35 °C
Standards	NF C 61-314
Product certifications	LCIE: NF 604966
IK degree of protection	IK04
IP degree of protection	IP21D
Environmental characteristic	Ammonia Alcohol Acetone
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**