



Main

Range of product	Mureva Styl
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

Complementary

Device mounting	Surface
Switch function	2-way
Actuator	Rocker
Rated current	10 AX
Load type	Load for energy saving lamps with ballast: 100 W
[Ue] rated operational voltage	250 V AC
Local signalling	LED (blue)
Current consumption	0.15 mA at 250 V
Condition of use	Indoor/Outdoor
Material	ABS (acrylonitrile butadiene-styrene) SEBS Brass
Fixing mode	By screws
Clamping connection capacity	1.5...2.5 mm ² for rigid cable(s) 1.5...2.5 mm ² for stranded cable(s) 1.5...2.5 mm ² for flexible cable(s)
Wire stripping length	13 Mm
Cable entry	Easy valve access diameter: 6...20 mm
Height	76 Mm
Width	76 Mm
Depth	64 Mm
Projecting depth	64 Mm

Environment

Quality labels	EAC AENOR CE NF
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Standards	EN 60669-1

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

Product Life Status : **Commercialised**