



Main

Range	Odace
Product or component type	Switch
Device presentation	Mechanism with plastic fixing frame
Switch application	Roller blind
Switch additional information	Mechanical and electrical interlock between up/down
Quantity per set	Set of 1
Condition of use	Indoor

Complementary

Device mounting	Flush
Switch function	3 positions
Number of rocker	3
Actuator	Rocker
Fixing mode	Screws
Colour tint	Anthracite
Rated current	6 AX at 250 V AC 50/60 Hz
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un
Number of terminals	3 screwless terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for rigid cable(s) 1 x 1.5...2 x 2.5 mm ² for flexible cable(s) 1 x 1.5...2 x 2.5 mm ² for stranded cable(s)
Wire stripping length	12 Mm
Material	Thermoplastic ABS-UV stabilised: centre plate PBT (polybutylene terephthalate) GF30: support frame PC (polycarbonate) GF10 FR: casing
Height	71 Mm
Width	71 Mm
Depth	43 Mm
Embedding depth	31.2 Mm
Net weight	0.048 Kg

Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	5...35 °C
Standards	EN 60669-1 2006/95/EEC
IK degree of protection	IK04

IP degree of protection	IP21D
Environmental characteristic	Bleach UV resistant Acetone Window-cleaning fluid Alcohol Oil Ammonia Liquid soap Petrol
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------