




Light Source Technical DataSheet

EAN	3276007812190
Product Supplier reference	HCL-292-400-W
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	INSPIRE
Replaceability of Light source	non-replacable
Replaceability of separate control gears	by qualified person
Light sources maker model	HCL-292-400
Link to EU Product Data base	https://eprel.ec.europa.eu/screen/product/lightsources/2922025
Spectral power distribution in the range 250 nm to 800 nm. at full-load	 <p>The graph shows the spectral power distribution (SPD) of the light source. The x-axis represents wavelength in nanometers (nm), ranging from 350 to 1000. The y-axis represents relative power, ranging from 0.0 to 1.0. There is a sharp peak at approximately 450 nm (blue) and a broad, multi-colored spectrum (rainbow) extending from approximately 450 nm to 700 nm. The total power is 1.0019440W/nm.</p>
The reference control settings, and instructions on how they can be implemented,	
If the light source contains mercury: instructions on how to clean up the debris in case of accidental breakage	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for advice on recycling.
Driver maker model	HCL-292-D
Maximum output power of the driver (for HL, LED and OLED) or the power of the light source for which the driver is intended (for FL and HID) ;	6
Type of light source(s) for which is intended	LED
Efficiency in full-load	0.9
No-load power (Pno) (W)	N/A
Standby power (Psb) (W)	N/A
Standby power (Pnet) (W)	N/A
Driver suitable for dimming :	no