
		PRODUCT INFORMATION SHEET (ANNEX 5)	Creation date (dd/mm/yyyy) :	29/08/2024
			Last update date (dd/mm/yyyy) :	29/08/2024
1	General information	Supplier's name or trade mark	XIAMEN GUANG PU ELECTRONICS CO.,LTD	
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN	
3		Model Identifier - Luminaire Supplier reference	*GPCL-G07-E30-18-811-RN-A2P-B*	
4		Light sources maker model	*GPCL-G07-E30-18-811-RN-A2P-B*	
5		Date of placement on the market	*18/02/2025*	
6	Type of light source:	Lighting technology used:	LED	
7		Light source cap type (or other electric interface)	/	
8		Non-directional (NDLS) or directional (DLS):	NDLS	
9		Mains (MLS) or non-mains (NMLS):	NMLS	
10		Connected light source (CLS):	no	
11		Colour-tuneable light source:	no	
12		Envelope:	no	
13		High luminance light source:	no	
14		Anti-glare shield:	no	
15		Dimmable:	second	
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h)	15	KWh/1000h
17		Energy efficiency class	D	
18		**Useful luminous flux (Φuse)**, indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm	2200	360
19		Correlated colour type	range	
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4000	K
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal	15.0	W
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal	0.00	W
23		Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal	0.00	W
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)		
26		Height (mm)	261.00	mm
27		Width (mm)	261.00	mm
28		Depth (mm)	21.00	mm
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)	GPCL-G07-E30-18-811-RN-A2P-B_spectral power distribution.jpg 	
30		Claim of equivalent power	yes	
31		If yes, equivalent power (W)	136	W
32		Chromaticity coordinates (x and y)	"0,3800;0,3800"	
33	Parameters directional light sources:	Peak luminous intensity (cd)		cd
34		Beam angle in degrees (no decimal), or the range of beam angles that can be set		Degrees
35	Parameter for LED and OLED light sources:	R9 colour rendering index value		
36		Survival factor rounded to the second decimal *(>0.xx)*	0.90	
37		Lumen maintenance factor rounded to the second decimal *(>0.xx)*	0.96	
38	Parameters for LED and OLED mains lights sources:	displacement factor (cos φ1) rounded to the second decimal	-	
39		Colour consistency in McAdam ellipses	-	
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	
41		If yes then replacement claim (W) (no decimal)		W
42		Flicker metric (Pst LM) rounded to the first decimal	-	
43		Stroboscopic effect metric (SVM) rounded to the first decimal		
44	Technical documentation name (in case of light source product)			
45	Light source removing instruction name (in case of containing product)		GPCL-G07-E30-18-811-RN-A2P-B removing instruction	