

## **DECLARATION OF PERFORMANCE**

No: 001

1. Unique identification code of the product

## DRY-PRESSED CERAMIC TILES, WITH WATER ABSORTION E > 10,0 %, TYPE 1

2. Intended use

## FOR INTERNAL WALLS

3. Name and adress of Manufacturer

BALDOCER, S.A. Ctra. La Pobla Tornesa – Vall d'Alba, km.4 12192 Vilafamés (Castellón) SPAIN

**4.** Systems of AVCP: System 4

5. Harmonised standard: EN 14411: 2012

6. Declared performances

ESSENTIAL CHARACTERISTICS	PERFORMANCES
Reaction to fire	A1
Release of dangerous substance, for: - Cadmium - Lead - Others	NPD
Bond strength/adhesion, for: - Cementitious adhesives - Dispersion adhesives - Reaction resin adhesives - Mortar	Type C2: > 1 N/mm² NPD NPD NPD
Thermal shock	NPD
Durability for: - Internal use - External Use: freeze-thaw resistance	Pass NPD

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Felipe Peraire Palos General Manager