

Product Information

tesa® 4352 Allround Mask



tesa® 4352 Allround Mask: for superior quality interior and outdoor work. The combination of a flat paper backing with a balanced acrylic adhesive compound guarantees sharp paint edges and a residue-free removal up to 4 weeks indoors and up to 2 weeks outdoors.

Main Application

- Sharp edges to paint and lacquer
- No paint bleeding
- For smooth and slightly textured surfaces
- Traceless removal after up to 4 weeks indoors and after up to 2 weeks outdoors

Technical information (average values)

The values in this section should be considered as average figures or typical only and should not be used for specification purposes.

Technical Data:

Backing material	Smooth paper	Elongation at break	*12%
Type of adhesive	Acrylic	Tensile strength	*37 N/cm
Total thickness	*125 µm		

Adhesion to:

Steel	*1.7 N/cm	
-------	-----------	--

Properties:

Hand tearability	●●●●	Sharp color edge	●●●●
Suitable for sensitive surfaces	●●●	Wet removability	●●●●
Suitable for rough surfaces	●●●	Cold removability	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

*Data has not been statistically validated yet

Additional Information & Pictures



NART	Article Description	Dimension
04352-00000-00	tesa® Allround Mask (Western Europe)	50m : 19mm
04352-00005-00	tesa® Allround Mask (Eastern Europe)	50m : 19mm
04352-00001-00	tesa® Allround Mask (Western Europe)	50m : 25mm
04352-00006-00	tesa® Allround Mask (Eastern Europe)	50m : 25mm
04352-00002-00	tesa® Allround Mask (Europe + Arabic)	50m : 30mm
04352-00003-00	tesa® Allround Mask (Europe + Arabic)	50m : 38mm
04352-00004-00	tesa® Allround Mask (Europe + Arabic)	50m : 50mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless, tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.