


L

			BS 14.4 LT	BS 18 LT	BS 14.4 LT Quick	BS 18 LT Quick	SB 18 LT
	*1)Serial Number		02100...	02102...	02101...	02104...	02103...
U	V		14,4	18	14,4	18	18
n ₀	/min, rpm	1	0 - 400	0 - 450	0 - 400	0 - 450	0 - 450
		2	0 - 1450	0 - 1600	0 - 1450	0 - 1600	0 - 1600
M ₁	Nm (in-lbs)		27 (239)	34 (301)	27 (239)	34 (301)	34 (301)
M ₃	Nm (in-lbs)		50 (442.5)	60 (531)	50 (442.5)	60 (531)	60 (531)
M ₄	Nm (in-lbs)	1	0,7 - 8 (6.2 - 70.8)	0,7 - 8 (6.2 - 70.8)	0,7 - 8 (6.2 - 70.8)	0,7 - 8 (6.2 - 70.8)	0,7 - 8 (6.2 - 70.8)
D ₁ max 	mm (in)		13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)
D ₂ max 	mm (in)		35 (1 3/8)	38 (1 1/2)	35 (1 3/8)	38 (1 1/2)	38 (1 1/2)
D ₃ max 	mm (in)	2	-	-	-	-	13 (1/2)
s	/min, bpm		-	-	-	-	24000
m	kg (lbs)		1,7 (3.7)	1,8 (4)	1,8 (4)	1,9 (4.2)	1,9 (4.2)
G	UNF(in)		1/2" - 20 UNF	1/2" - 20 UNF	1/2" - 20 UNF	1/2" - 20 UNF	1/2" - 20 UNF
D _{max}	mm (in)		13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)	13 (1/2)
a _{h, ID} - h _{h, ID}	m/s ²		-	-	-	-	-
a _{h, D} - h _{h, D}	m/s ²		< 2,5 / 1,5	-	-	-	-
a _{h, S} - h _{h, S}	m/s ²		< 2,5 / 1,5	-	-	-	-
L _{pA} /K _{pA}	dB(A)		73 / 3	73 / 3	73 / 3	73 / 3	91 / 3
L _{WA} /K _{WA}	dB(A)		84 / 3	84 / 3	84 / 3	84 / 3	102 / 3

 → 12.

M


 *2) 2014/30/EU, 2006/42/EC, 2011/65/EU
 *3) EN 60745-1:2009+A11:2010, EN 60745-2-1:2010, EN 60745-2-2:2010, EN 50581:2012

2018-02-01, Bernd Fleischmann *ppa. B.F.*
 Direktor Produktentstehung & Qualität (Vice President Product Engineering & Quality)
 *4) Metabowerke GmbH - Metabo-Allee 1 - 72622 Nuertingen, Germany

 → 1.