

南京海关危险货物与包装检测中心国家化学品分类鉴别与评估重点实验室



Report No.: DG2150563E



Design Report of Safety Data Sheet

		D	ate: 2021/07/05					
Name of the sample	Rechargeable Li-ion Battery US5000 48V 100Ah 4800Wh 检验检测专用章							
Applicant	Pylon Technologies Co., Ltd.							
Supplier	Pylon Technologies Co., Ltd.							
Composition of the sample	Lithium Iron Phosphate; Graphite; Copper; Aluminium; Poly(vinylidene difluoride); Carbon black; Polyacrylic acid; Lithium hexafluorophosphate; Nickel							
Warranty of Design	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) Eighth revised edition							
	Design Result of SDS please see next page.							
Designer	华雯	Approver	王和太					

Notes: This SDS is valid before the implementation of the ninth revised edition GHS.



地址:中国.常州市天宁区青洋北路 47 号 电话 (Tel):+86-519-85152626,85807785

Add: 47 Qingyang North Road, Tianning District, Changzhou, China

邮编 (P.C.): 213000

SAFETY DATA SHEET

Rechargeable Li-ion Battery US5000 48V 100Ah 4800Wh

Pylon Technologies Co., Ltd.

According to GHS (Eighth Revised Edition)



Section 1 Product and Company Identification

> Product Identifier

Product Name Rechargeable Li-ion Battery US5000 48V 100Ah 4800Wh

Synonyms

nonyms

CAS No. Not applicable

EC No. Not applicable

Molecular Formula Not applicable

> Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Relevant Identified

Uses

Please consult manufacturer.

Uses Advised Against Please consult manufacturer.

> Details of the Supplier of the Safety Data Sheet

Applicant Name Pylon Technologies Co., Ltd.

Application Address No.73, Lane 887, Zu Chongzhi Road, Zhangjiang Hi-Tech Park Pudong,

Shanghai 201203, China

Applicant Post Code 200120

Applicant Telephone +86-21-51317697 **Applicant Fax** +86-21-51317698

Applicant E-mail wang.zhonghe@pylontech.com.cn

Supplier Name Pylon Technologies Co., Ltd.

Supplier Address

Plant 8, No.505 Kunkai Road, JinXi Town, Kunshan City, Jiangsu Province,

PEOPLE'S REPUBLIC OF CHINA, 215324

Supplier Post Code 215300

Supplier Telephone +86-21-51317697 **Supplier Fax** +86-21-51317698

Supplier E-mail wang.zhonghe@pylontech.com.cn

> Emergency Phone Number

Emergency Phone

Number +86-21-51317699

Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the eighth revised edition):

> GHS Hazard Class

This product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev.8 (2019) Part 1.3.2.1.1]

> GHS Label Elements

Pictogram

Not applicable

Signal Word

Not applicable

> Hazard Statements

Not applicable

> Precautionary Statements

Prevention

Do not open or disassemble.

Do not expose to high temperatures or open fire.

Do not mix with batteries of varying sizes, chemistries or types.

Avoid using external impact battery.

Response

Not applicable

Storage

Store under roof in cool, dry, well-ventilated areas.

Disposal

Dispose of contents/container in accordance with local/regional/national/

international regulations.

Section 3 Composition/Information on Ingredients

Component	Concentration (weight percent, %)	CAS No.	EC No.
Lithium Iron Phosphate	Commercial secrets	15365-14-7	604-917-2
Graphite	Commercial secrets	7782-42-5	231-955-3
Copper	Commercial secrets	7440-50-8	231-159-6
Aluminium	Commercial secrets	7429-90-5	231-072-3
Poly(vinylidene difluoride)	Commercial secrets	24937-79-9	200-867-7
Carbon black	Commercial secrets	1333-86-4	215-609-9
Polyacrylic acid	Commercial secrets	9003-01-4	202-415-4
Lithium hexafluorophosphate	Commercial secrets	21324-40-3	244-334-7
Nickel	Commercial secrets	7440-02-0	231-111-4

Section 4 First Aid Measures

> Description of First Aid Measures

General Advice

Immediate medical attention is required. Show this safety data sheet (SDS) to

DG 2159

DØ21595

the doctor in attendance.

Rinse thoroughly with plenty of water for at least 15 minutes and con-**Eye Contact**

physician if feel uncomfortable.

Take off contaminated clothing and shoes immediately. Washoff with plenty of **Skin Contact**

water for at least 15 minutes and consult a physician if feel incomfortable Do not induce vomiting. Never give anything by mouth to an unconscious

person. Call a physician or Poison Control Center immediately.

Move victim into fresh air. If breathing is difficult, give oxygen. Do not use

mouth to mouth resuscitation if victim ingested or inhaled the substance. If not

breathing, give artificial respiration and consult a physician immediately. Protecting of Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

First-aiders

Ingestion

Inhalation

> Most Important Symptoms and Effects, both Acute and Delayed

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

> Indication of Any Immediate Medical Attention and Special Treatment Needed

1 Treat symptomatically.

2 Symptoms may be delayed.

Section 5 Fire Fighting Measures

> Extinguishing Media

Suitable Extinguishing Media

Unsuitable **Extinguishing Media** Dry chemical, carbon dioxide or alcohol-resistant foam.

Do not use a solid water stream as it may scatter or spread fire.

> Specific Hazards Arising from the Substance or Mixture

- Containers may explode when heated.
- 2 Fire exposed containers may vent contents through pressure relief valves.
- May expansion or decompose explosively when heated or involved in fire.

> Advice for Firefighters

- As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and 1 full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- Prevent fire extinguishing water from contaminating surface water or the ground water system.

Section 6 Accidental Release Measure

> Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Ensure adequate ventilation. Remove all sources of ignition.
- 2 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

> Environmental Precautions

- Prevent further leakage or spillage if safe to do so. 1
- 2 Discharge into the environment must be avoided.

> Methods and Materials for Containment and Cleaning Up

Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage contain a spill by bunding.

Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Section 7 Handling and Storage

> Precautions for Handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.
- 5 Take precautionary measures against static discharges.

> Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

Section 8 Exposure Controls/Personal Protection

> Control Parameters

Occupational Exposure Limit Values

Component	Country/Region	Limit Value	- Eight Hours	Limit Value	- Short Term
Component	Country/Region	ppm	mg/m³	ppm	mg/m³
Graphite 7782-42-5	USA - OSHA	-	15	-	-
	South Korea	-	2	-	-
	Ireland		10	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	2.5	-	5
	Australia	-	3 (4)	-	-
	The Netherlands	-	0.1	-	-
Copper	Poland	-	0.2	-	-
7440-50-8	Latvia	-	0.5	-	1
	Germany (DFG)	-	0.01	-	ppm mg/m³ - - - - - - - - - - - - - - - - - - - - - - - - - - - -
	USA - OSHA	-	15	-	-
	South Korea	-	10	-	-
Aluminium 7429-90-5	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-

Rechargeable Li-ion Battery	US5000 48V 100Ah 4800Wh
-----------------------------	-------------------------

Rechargeable Li-ion	Battery US5000 48V 10	0Ah 4800Wh			版的2559563E
	USA - OSHA	-	3.5	- /	The state of the s
	South Korea	-	3.5	-	建 全 差
Carbon black	Ireland	-	3.5	-	版 7
1333-86-4	France	-	3.5	-	检验检测专用章
	Denmark	-	3.5	-	7
	Australia	-	3	-	-
	USA - OSHA	-	1	-	-
	South Korea	=	1	-	-
Nickel	Ireland	-	0.5	-	-
7440-02-0	Hungary	-	0.1	-	0.1
	Denmark	-	0.05	-	0.1
	Australia	_	1	_	-

Biological Limit Values

Component	omponent Source		Biological limits Sampling time		remar k
		Fluorine/urine	8mg/L	end of shift	

Monitoring Methods

EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

GBZ/T 160 Determination of toxic substances in workplace air(Series effective standard) and GBZ/T 300 Determination of toxic substances in workplace air(Series standard).

> Engineering Controls

- Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- Set up emergency exit and necessary risk-elimination area.

Personal Protection Equipment

Eye Protection Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).

Wear protective gloves (such as butyl rubber) , passing the tests according to **Hand Protection** EN 374(EU), US F739 or AS/NZS 2161.1 standard.

If exposure limits are exceeded or if irritation or other symptoms are

Respiratory protection experienced, use a full-face respirator with multi-purpose combination (US) or

type AXBEK (EN 14387) respirator cartridges.

Skin and **Body**

Wear fire/flame resistant/retardant clothing and antistatic boots. Protection

Section 9 **Physical and Chemical Properties**

Appearance: Lithium ion Battery, individually

packaged

Odor Threshold: No information available

Melting Point/Freezing Point (°C): No information Initial Boiling Point and Boiling Range (°C): No

Flash Point (°C)(Closed Cup): Not applicable

Flammability: No information available

Odor: No information available

pH: No information available

information available

Evaporation Rate: Not applicable

Upper/lower explosive limits[%(v/v)]: Upper limit : No information available ; Lower limit : No information Vapor Pressure (KPa): Not applicable

Relative Density(Water=1): No information

available

n-Octanol/Water Partition Coefficient: No

information available

Decomposition Temperature (°C): No information

available

Particle characteristics: No information available

available

Relative Vapour Density(Air = 1 : Not app

Solubility: No information available

Auto-Ignition Temperature (°C): No information

available

Kinematic Viscosity (mm²/s): Not applicable

Section 10 Stability and Reactivity

Reactivity Contact with incompatible substances can cause decomposition or other

chemical reactions.

Chemical Stability

Stable under proper operation and storage conditions. Possibility of

Mixtures with metallic acetylene, when heated, cause a fire or incandescence. **Hazardous Reactions** Reacts severely with halogens, interhalogens or other strong oxidants, or

causes a fire. Ultrafine powder will self-ignite in the air at room temperature.

Conditions to Avoid Incompatible materials, heat, flame and spark.

Incompatible Materials Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous

oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates,

inorganic peroxides, metal oxides and peroxyformic acid. Halogen,

interhalogen, strong oxidant, water and acids. Oxidants, halogen, interhalogen

and mercury.

Hazardous

Decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11 Toxicological Information

> Acute Toxicity

Component CAS No.		LD ₅₀ (Oral)	LD ₅₀ (Dermal)	LC ₅₀ (Inhalation, 4h)
Carbon black	1333-86-4	> 15400mg/kg(Rat)	> 3000mg/kg(Rabbit)	No information available
Polyacrylic acid	9003-01-4	2500mg/kg(Rat)	No information available	No information available

> Skin Corrosion/Irritation

No information available

> Serious Eye Damage/Irritation

No information available

> Skin Sensitization

No information available

> Respiratory Sensitization

No information available

> Germ Cell Mutagenicity

No information available

> Carcinogenicity

ID	CAS No.	Component	IARC	NTP	
1	15365-14-7	Lithium Iron Phosphate	Not Listed	Not Listed	
2	7782-42-5	Graphite	Not Listed	Not Listed	
3	7440-50-8	Copper	Not Listed	Not Listed	
4	7429-90-5	Aluminium	Not Listed	Not Listed	
5	24937-79-9	Poly(vinylidene difluoride)	Not Listed	Not Listed	
6	1333-86-4	Carbon black			
7	9003-01-4	Polyacrylic acid	Category 3	Not Listed	
8	21324-40-3	Lithium hexafluorophosphate	Not Listed	Not Listed	
9	7440-02-0	Nickel	Category 2B	Not Listed	

> Reproductive Toxicity

No information available

> Reproductive Toxicity (Additional)

No information available

> STOT-Single Exposure

No information available

> STOT-Repeated Exposure

No information available

> Aspiration Hazard

No information available

Section 12 Ecological Information

> Acute Aquatic Toxicity

Component	Component CAS No. Fish		Crustaceans	Algae		
Copper	7440-50-8	LC ₅₀ : 0.665mg/L (96h)(Fish)	EC ₅₀ : 0.02mg/L (48h)	ErC ₅₀ : 7.9mg/L (96h)		
Aluminium	7429-90-5	LC ₅₀ : 1.55mg/L (96h)(Fish)	No information available	No information available		
Nickel	7440-02-0	LC ₅₀ :40mg/L (96h)(Fish)	EC ₅₀ : 1mg/L (48h)	No information available		



> Chronic Aquatic Toxicity

No information available

> Others

Persistence and Degradability **Bioaccumulative Potential**

No information available

No information available

Mobility in Soil No information available

Lithium Iron Phosphate does not meet the criteria for PBT and vPvB according

to Regulation (EC) No 1907/2006, annex XIII.

Graphite does not meet the criteria for PBT and vPvB according to Regulation

(EC) No 1907/2006, annex XIII.

Copper does not meet the criteria for PBT and vPvB according to Regulation

(EC) No 1907/2006, annex XIII.

Aluminium does not meet the criteria for PBT and vPvB according to Regulation

(EC) No 1907/2006, annex XIII.

Results of PBT and **vPvB** Assessment

Poly(vinylidene difluoride) does not meet the criteria for PBT and vPvB

according to Regulation (EC) No 1907/2006, annex XIII.

Carbon black does not meet the criteria for PBT and vPvB according to

Regulation (EC) No 1907/2006, annex XIII.

Polyacrylic acid does not meet the criteria for PBT and vPvB according to

Regulation (EC) No 1907/2006, annex XIII.

Lithium hexafluorophosphate does not meet the criteria for PBT and vPvB

according to Regulation (EC) No 1907/2006, annex XIII.

Nickel does not meet the criteria for PBT and vPvB according to Regulation (EC)

No 1907/2006, annex XIII.

Section 13 **Disposal Considerations**

Waste Chemicals

Before disposal should refer to the relevant national and local laws and

regulation. Recommend the use of incineration disposal.

Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible.

Refer to Waste chemicals and Contaminated packaging.

Contaminated **Packaging** Disposal Recommendations

Section 14 Transport Information

Transporting Label



Marine pollutant

None

UN Number

3480

UN Proper Shipping

Name

LITHIUM ION BATTERIES(including lithium ion polymer batteries)

Transport Hazard Class

9

Transport Subsidiary Hazard Class

NONE

Packing Group Packagings shall conform to

Packagings shall conform to the packing group II performance level

According to United Nations Recommendations on the Transports of Dangerous Goods•Model Regulations, Lithium batteries could be transported

in accordance with the classification conclusions of this report when meet the

requirements of UN38.3 test.

Section 15 Regulatory Information

> International Chemical Inventory

Report remarks

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS	ENCS
Lithium Iron Phosphate	√	√	√	×	×	×	V	×	×
Graphite	√	√	√	√	√	√	√	V	×
Copper	√	√	√	√	√	√	√	√	×
Aluminium	√	√	√	√	√	√	√	√	×
Poly(vinylidene difluoride)	×	√	√	√	√	√	√	√	√
Carbon black	√	√	√	√	√	√	√	√	×
Polyacrylic acid	√	√	√	√	√	√	×	√	√
Lithium hexafluorophosph ate	√	√	×	V	×	√	√	√	×
Nickel	√	√	√	√	√	√	V	√	×

[EINECS] European Inventory of Existing Commercial Chemical Substances.

[TSCA] United States Toxic Substances Control Act Inventory.

[DSL] Canadian Domestic Substances List.

[IECSC] China Inventory of Existing Chemical Substances.

[NZIoC] New Zealand Inventory of Chemicals.

[PICCS] Philippines Inventory of Chemicals and Chemical Substances.

[KECI] Existing and Evaluated Chemical Substances.

[AICS] Australia Inventory of Chemical Substances.

[ENCS] Existing And New Chemical Substances.

Note

"\" Indicates that the substance included in the regulations

"x" That no data or included in the regulations

Section 16 Additional Information

 Creation Date
 2021/07/05

 Revision Date
 2021/07/05

Reason for Revision

> Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 8th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

DG 27595

检验检测专用章



南京海关危险货物与包装检测中心 国家化学品分类鉴别与评估重点实验室





Terms of the Using of the Report

- The report is issued by DPTC according to the information of the chemicals and the information of it shipping provided by the applicant (shipper or his agent).
- According to the demand of this SDS, DPTC requires the applicant to provide true and exact sample and data. 2.
- 3. Information from applicant is the key of this Label, so the center will not respond for the wrong of applicant.
- Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested. 4.
- This report will be effective only after it is signed by the inspector, approver and stamped by DPTC. 5.
- 6. Our center guarantees the objectivity and fairness of this report, and carries out confidentiality obligations on business secrets such as business information, technical documents and so on.
- 7. The partly duplicating of this report is prohibited without the written approver of DPTC.
- 8. The report is invalid when anything of the following happens-illegal transfer, embezzlement, imposture, modification or tampering in any media form.
- 9. The authenticity of the certificate can be checked by scanning the QR code of this certificate.

