

ToLEDo T8 CCG and AC

TOLEDO T8 V6 2FT 10W 1000LM 840 RL
0028284



Características del producto

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps • Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes • High lumen package - 1000lm • High lumen efficacy - 100 lm/W • Energy rating - A+ • Switching cycles - 200,000X • Average life 40,000 hours lifespan (L70 F50) • Wide beam angle - 220° • High power factor - 0.90 • Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications • Suitable for operation with electromagnetic gears and direct mains operation (220-240V) • 3-Year warranty.



DESCRIPCIÓN DEL PRODUCTO

Nombre del producto	TOLEDO T8 V6 2FT 10W 1000LM 840 RL
Tecnología	LED
Potencia (clasificada) (W)	10
Cap/Base	G13
General application	Hospitality, Logistics & Industry, Residential & Consumer,
ETIM Class	EC001959
FI del número electrónico	4940739
Warranty	5 years
Flujo luminoso (nominal) (lm)	1000
Temperatura de color (K)	4000
Color de la luz	Cool White
IRC (Ra)	80
Wattage (W)	10
Tensión (V)	230
Dimmable	No
Average life (Nominal) (h)	40000
Product EAN number	5410288282848

TABLA DE DATOS

Informacion General

Nombre del producto	TOLEDO T8 V6 2FT 10W 1000LM 840 RL
Tecnología	LED
Potencia (clasificada) (W)	10
Cap/Base	G13
General application	Hospitality, Logistics & Industry, Residential & Consumer,
ETIM Class	EC001959
FI del número electrónico	4940739
Warranty	5 years

Datos ópticos

Flujo luminoso (nominal) (lm)	1000
Flujo luminoso (clasificado) (lm)	1000

ToLEDo T8 CCG and AC

TOLEDO T8 V6 2FT 10W 1000LM 840 RL
0028284

Temperatura de color (K)	4000
Color de la luz	Cool White
IRC (Ra)	80
Mantenimiento de flujo luminoso al final de la vida útil nominal (lm)	70

Datos eléctricos

Wattage (W)	10
Tiempo de encendido (máx.) (s)	0.5
Tiempo de calentamiento al 60% de plena luz (máx.) (s)	0.5
Tensión (V)	230
Lamp power factor	0.9
No. Of switching cycles before premature failures	>200000
Dimmable	No
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	10

Información de vida útil

Average life (Nominal) (h)	40000
Promedio de vida útil (h) - L70/B50	40000

Datos físicos

Peso (kg)	0.105
-----------	-------

Empaquetado

Descripción del paquete	Carton
Product EAN number	5410288282848
Longitud del embalaje individual(cm)	65.2
Anchura única del embalaje (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288282845
Cantidad del embalaje por cajas	10
Packaging outer length / height (cm)	68.7
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.7

Información de seguridad

Instrucciones de limpieza en caso de rotura	Not applicable
Lámpara para usos especiales	No
No es adecuado para iluminación doméstica	Sí
Mensaje de seguridad	Suitable for totally enclosed fixture

ToLEDo T8 CCG and AC
TOLEDO T8 V6 2FT 10W 1000LM 840 RL
0028284

