



guttatuil Standard

Length:	2000 mm
Width:	1055 mm
Thickness:	2,4 mm
Heigh of corrugation:	32 mm
Pitch of corrugation:	96 mm
Gross surface:	2,11 m ²
Weight:	5,2 kg
Weight / m ² :	2,45 kg/m ²
Corrugations + Flat parts:	9 +4
Bending under downward load:	> 500 N/m ²
Impact strength:	Not applicable
Tearing strength:	Not applicable
Water impermeability:	Pass
Proportion of bitumen:	> 40%
Homogeneity:	Pass
Water absorption:	< 20%
Water vapor permeability - EN ISO 12572:	< 4000μ
Water impermeability after ageing:	Pass
Tearing strength after ageing:	not specified
Thermal coefficient:	not specified
Reaction to fire - EN 13501-1:	E
Color:	Asphalt
Installation:	Special installation conditions are required. Read the installation instructions.
Warranty:	Factory warranty 10 years according to our warranty conditions
Note:	Subject to technical changes without notice.

05.10.2018

Gutta Werke GmbH | Bau- und Heimwerkerprodukte | Bahnhofstraße 51-57 | 77746 Schutterwald

Tel.: 0781 609-220 | Fax: 0781 609-3220 | E-mail: technik@gutta.com

www.gutta.com