

PRODUCT-DETAILS

N2260.3 PL

N2260.3 PL - LED rotatory/push dimmer - 2M -Silver



| _ | | _ |
|---------|-----------|------|
| General | l Informa | tion |

N2260.3 PL **Extended Product Type** Product ID 2CLA226030N1301 EAN 8427238138336 **Catalog Description** N2260.3 PL - LED rotatory/push dimmer - 2M - Silver

Rated voltage: 230 Vac ± 10% Frequency: 50 Hz (Nominal power: 250 W/VA) / 60 Hz (Nominal power: 200 W/VA)

Power (min./max load): - LEDi: 2 / 100 W/VA (max. 10 lamps)

- Dimmable energy saving lamps: 2 / 100 W/VA (max. 10 lamps)

- LV LEDi with transformer (only type L or LC): 4 / 100 W/VA (max. 10 lamps)

- Incandescent lamps: 10 / 250 W/VA

- Halogen lamps: 10 / 250 W/VA

- LV halogen with transformer (only type L or LC): 10 / 250 W/VA (max. 10 lamps)

2 wire connection

Optional: auxiliary on/off with 2-way switch N2X02

Indicator LED lamp included

Back-up fuse: Electronic

Overload protection: Electronic Ambient temperature: 0°C to +35°C

Size: 2 modules.

Ordering

Long Description

| EAN | 8427238138336 |
|------------------------|---------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |

| Dimensions | |
|--------------------|---------|
| Product Net Width | 44 mm |
| Product Net Height | 44 mm |
| Product Net Weight | 0.08 kg |

| Container Information | |
|-----------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 0.076 m |
| Package Level 1 Height | 0.064 m |
| Package Level 1 Depth / Length | 0.076 m |
| Package Level 1 Gross Weight | 0.08 kg |
| Package Level 1 EAN | 8427238138336 |

| Environmental | |
|---------------|---------------------|
| Ambient Air | Operation -5 +35 °C |
| Temperature | Storage -5 +50 °C |

| Actuator Type | Turn button |
|---------------------------------|--|
| Color | Silver |
| Connection Type | Screw |
| Degree of Protection | IP20 |
| Frequency (f) | 5060 Hz |
| Load Type | Universal and LED Retrofit |
| Material | Material quality: Thermoplastic Material: Plastic |
| Mounting Type | Flush mounted (plaster) |
| Product Main Type | Zenit |
| Product Name | LED rotatory/push dimmer - 2M - Silver |
| Rated Voltage (U _r) | 230230 V |
| Replaced Product ID (OLD) | 2CL0N226033 |
| Surface Finishing | Surface protection: Decor Surface finishing: Matt |

| Certificates and Declarations (Document Number) | |
|---|-----------------|
| Data Sheet, Technical Information | 9AKK10103A5108 |
| Declaration of Conformity - CE | 9AKK106930A5901 |
| Instructions and Manuals | 2CLX226039N1001 |

| Classifications | |
|-----------------|--|
| ETIM 5 | EC000025 - Dimmer |
| ETIM 6 | EC000025 - Dimmer |
| ETIM 7 | EC000025 - Dimmer |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

N2260.3 PL 3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ Modular\ Range\ -\ Niessen \rightarrow Design\ Zenit \rightarrow Flush\ Mounted\ Inserts\ with\ Cover\ Plate \rightarrow Dimmers$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Light\ /\ LoadControl \rightarrow Electronic\ Rotary\ /\ Push\ Button\ Dimmer\ (all\ Loads\ incl.\ LED,\ DALI) \rightarrow Push\ Button\ Dimmer\ -\ Flush\ Mounted \rightarrow Dimmers$

