

Barcelona, 25th March 2015**DECLARATION OF CONFORMITY****PRESINOX EXTENSIBLE FF DN12 and MF DN16**

Suitable for the connection of fixed appliances to gas domestic network. MOP ≤ 0.4 bar

Product Standard: **UNE 60713/1**Certified product: **AT-017-05/2075-2012,****EUROPEAN INSTITUTE OF THERMAL SCIENCES Bucharest****MATERIALS**Connecting fittings: **NUTS – BRASS / NICKEL PLATED;
NIPPLES – STAINLESS STEEL**Threads: **G1/2" and G3/4" (ISO 228/1)**Pipe: **Corrugated annealed flexible stainless steel pipe**Seals: **Rubber NBR seals suitable for gas**Cover: **Polyolefin YELLOW outer cover****Size****FF DN12**

Internal diameter 10.0 mm

External Diameter 17.4 mm

MF DN16

Internal diameter 16.0 mm

External Diameter 21.6 mm

Performance

Suitable for GN - natural gas (2nd family gas) and GPL (3rd family gas)

Maximum working pressure 0.4 bar

Extensible up to +70% of original length,

Minimum bending radius 30 mm (DN12) and 45 mm (DN16)

Eva Fàbregas
TUCAI S.A.