

DECLARACION DE CONFORMIDAD/ DECLARATION OF CONFORMITY SI EN 10.204.-2.1								
CLIENTE/CLIENT:			Nº PEDIDO/PURCHASE Nº:			FECHA/DATE:		
CARACTERISTICAS DE PRODUCTO/PRODUCT CHARACTERISTICS 1/1								
PRODUCTO/PRODUCT								
TRIPLE TORSION GALVANIZADA / WIRE NETTING GALVANIZED TRIPLE TORSION PLASTIFICADA / WIRE NETTING PLASTIC COATED								
CARACTERISTICAS DEL ACERO/STEEL CHARACTERISTICS:								
TIPO/TYPE: C4D				NORMA/STANDARD: ISO 16120-2				
C (%)	Mn (%)	Si (%)	P (%)	S (%)				
≤ 0.06	0.30÷0.45	0.10÷0.20	≤ 0.030	≤ 0.030				
CARACTERISTICAS DE LOS ALAMBRES/WIRE CHARACTERISTICS:								
ALAMBRES/WIRES		DIAMETRO/ DIAMETER (mm)	RESISTENCIA/ TENSILE STRENGTH (N/mm²)	CAPA DE ZINC/ZINC COATED (gr/m²)				
WIRE		0.60	450 ÷ 550	≥ 20				
		0.70						
		0.80						
CARACTERISTICAS DEL RECUBRIMIENTO DE ZINC/ZINC COATING CHARACTERISTICS :								
TYPE OF ZINC: (Z1) de 99.995% Min.				TYPE OF ZINC ZINC BY STANDARD: EN 1179				
MASS OF ZINC: (gr/m²): In Wire Characteristics				MASS OF ZINC BY STANDARD: EN 10244-2				
CARACT. DEL RECUBRIMIENTO ORGANICO (PLASTIFICADO)/PLASTIC COATED CHARACTERISTICS:								
PRODUCT: GREEN PVC				PRODUCT BY STANDARD:				
DENSITY (Kg/m³): 1.28				DENSITY BY STANDARD:				
THICKNESS (mm): 0,2				THICKNESS BY STANDARD:				
CARACTERISTICAS DEL PRODUCTO/ PRODUCT CHARACTERISTICS:								
DIMENSIONES STANDARD GALVANIZADO/WIRE NETTING GALVANIZED STANDARD:								
TIPO/ TYPE	DIAMETRO/DIAMETER NOMINAL (mm) By standard: 10223 - 2	ALTURA/HEIGHT (m)						LONGITUD/ LENGTH
		500	800	1000	1200	1500	2000	
13	0.60	X		X		X	X	50 m
16		X		X				
19	0.60	X		X		X	X	
25	0.70	X	X	X		X	X	
31	0.80	X	X	X				
41				X		X	X	
51		X		X	X	X	X	
13	0.60			X				10 m
19	0.60	X		X				
51	0.80	X		X				
DIMENSIONES STANDARD PLASTIFICADO VERDE/WIRE NETTING PLASTIC COATED STANDARD (GREEN):								
TIPO/ TYPE	DIAMETRO/ DIAMETER NOMINAL (mm)	ALTURA/HEIGHT (m)						LONGITUD/ LENGTH
		500	800	1000	1200	1500	2000	
19	0.60	X		X				10M

HEAD OFFICE: Avenida del Príncipe de Asturias, s/n -33211 Gijón, Asturias, ESPAÑA Tel. (+34) 98 530 80 60 – Fax (+34) 98 531 38 09