

# DITASA

DISTRIBUIDORA DE TUBOS Y AISLAMIENTOS, S.A.

C/ Pico Almanzor, 14 - Pol. Ind. Valdecabañas  
Tfno: 91 871 81 60 / 61 - Fax 91 871 81 62  
28500 ARGANDA DEL REY (Madrid)  
E-mail: [ditasa@ditasa.es](mailto:ditasa@ditasa.es)  
Web: [www.ditasa.es](http://www.ditasa.es)

Madrid, 17/06/2024

Oggetto: COPPER BRASS presinsulated copper pipe conformity declaration

DITASA, accordingly with the following Italian laws:

DPR N° 1095, 03<sup>rd</sup> August 1968  
DPR N° 447, 6<sup>th</sup> December 1991

DECLARES

under its responsibility, that the pre-insulated copper pipe produced with brand COPPER BRASS for air conditioning appliances is according with the following requirements:

## COPPER PIPE

Type of copper: CU – DHP 99,9%  
Residual phosphor: between 0,015% and 0,040%  
EN 12735 - 1 (COPPER BRASS)

## INSULATION

closed cell, low density polyethylene expanded  
self extinguish Class 1, EUROCLASS 13501-1 BLS1D0  
Working temperature: -80° C / +98° C  
Coeff. Of water vapour dispersion: 5.482  
Thermal conductivity: 0,0397 W . m-1 . K-1  
CFC free  
ecological

# DITASA

DISTRIBUIDORA DE TUBOS Y AISLAMIENTOS, S.A.

C/ Pico Almanzor, 14 - Pol. Ind. Valdecabañas  
Tfno: 91 871 81 60 / 61 - Fax 91 871 81 62  
28500 ARGANDA DEL REY (Madrid)  
E-mail: [ditasa@ditasa.es](mailto:ditasa@ditasa.es)  
Web: [www.ditasa.es](http://www.ditasa.es)

## WORKING PRESSURE

1/4x0,63.....	44 bar
3/8x0,63	44
1/2x0,70	44
5/8x0,70	55

Insulated copper pipe comes with the following insulation wall thickness:

1/4.....	9,0mm
3/8	9,0mm
1/2	9,0mm
5/8	9,0mm

The above described product is guaranteed for the gas R407, R410 and R32.

DITASA releases this certificate for the permitted uses.

The conformity depends on the full respect of the laws in installation.

Fdo.

