

DECLARATION OF PERFORMANCE

No: 007

1. Unique identification code of the product

DRY-PRESSED CERAMIC TILES WITH THICKNESS <7,5MM, WITH WATER ABSORPTION E≤0,5%, TYPE 7

2. Intended use

FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS

3. Name and address of Manufacturer

DILMUN EMPRESARIAL, S.L.
Ctra. Pobla Tornesa – Vall d'Alba, km.4
12192 Vilafamés (Castellón) SPAIN

4. Systems of AVCP

4

5. Name and number of laboratory notified

NOT APPLY

6. Declared performances

ESSENTIAL CHARACTERISTICS	PERFORMANCES	TECHNICAL SPECIFICATION HARMONIZED
Reaction to fire	A1-A1 _{fl}	EN 14411: 2012
Release of dangerous substance, for: - Cadmium - Lead - Others	NPD	
Adhesion (N/mm ²)	> 1 N/mm ² with type C2 adhesives	
Slipperiness, as: Pendulum method according to ET CEN/TS 16165	NPD	
Thermal shock	Pass	
Durability for: - Internal use - External Use	Pass Pass	
Tactility	NPD	
Breaking strength (in ISO 10545-4)	Minimum 700N	

The performance of the product identified in point 1 is in conformity with the set of declared in point 6.

This declaration of conformity is issued under the sole responsibility of the manufacturer indicated in point 3.

Felipe Peraire Pates
General Manager
DILMUN EMPRESARIAL, S.L.
Ctra. La Pobla-Vall d'Alba km.4
12192 VILAFAMÉS
(Castellón)
B-98732001

Vilafamés, January 20th, 2015