




LUZ DE TRABAJO CON ALMACENAJE DE CABLE

Características de Producto


- Grado de protección IP65 para ambientes extremos
- Chips LED de alta eficiencia y larga vida
- Vidrio esmerilado templado
- Suministrado con 2.05m (20W) y 2.25m (30W) de cable H05RN-F
- Cómodo almacenaje de cable alrededor de la luz de trabajo.
- Gancho incluido para su uso en suspensión
- Luz de trabajo basculante
- Adecuado para decoración, proyectos de exterior e iluminación de trabajo.



LW19Y40



LW28Y40



CAT NO.	LUMINARIA (LÚMENES)	POTENCIA (W)	EFICIENCIA (Llm/w)	PESO (kg)	DIMENSIONES (mm)	CRI	RATIO IK	TENSIÓN DE ALIMENTACIÓN	FRECUENCIA DE ALIMENTACIÓN	RANGO TEMP. (C)	L/B VIDA UTIL
LW19Y40	1800	20	95	0,86	239x204x54	>80	IK06	220 - 240V	50	-20 +25	L90/B10
LW28Y40	2800	30	93	1,15	256x222x54	>80	IK06	220 - 240V	50	-20 +25	L90/B10

STANDARD	DESCRIPTION
EN 60598-1	Luminaires – General requirements
EN 60598-2-4	Luminaires – Portable
EN 61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions
EN 61000-3-3	Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes – EMC immunity requirements
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Luceco
LW19Y40

A
B
C
D
E
F
G

20
kWh/1000h

2019/2015

Luceco
LW28Y40

A
B
C
D
E
F
G

30
kWh/1000h

2019/2015

