

PROYECTOR LED SLIMLINE CON CAMBIO DE COLOR

Características de Producto

- Proyector doméstico adecuado para aplicaciones residenciales.
- Cuerpo de aluminio y cristal templado.
- Soporte robusto de acero para una sencilla instalación.
- Pre-cableado con manguera aislante H05RN-F.
- Cambio de temperatura de color 3000K-4000K-6500K a través de interruptor de pared.



CAT NO.	LUMINARIA LÚMENES	EFICIENCIA Lim/W	VOLTAJE	ÁNGULO DE APERTURA
EFLD10BCCBR	1150	115	220-240	110°
EFLD20BCCBR	2300	115	220-240	110°
EFLD30BCCBR	3300	110	220-240	110°
EFLD50BCCBR	5500	110	220-240	110°

Product Dimensions

CAT NO.	LARGO (mm)	ANCHO (mm)	ALTO (mm)
EFLD10BCCBR	114	29	94
EFLD20BCCBR	129	29	104
EFLD30BCCBR	184	30	148
EFLD50BCCBR	184	30	148

NORMATIVA	DESCRIPCIÓN
EN 60598-1	Luminaires – General requirements
EN 60598-2-5	Luminaires – Floodlights
EN 61000-3-2	Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes – EMC immunity requirements
EN 61347-1	Lamp controlgear - Part 1: General and safety requirements
EN 61347-2-13	Lamp controlgear - Part 2-13: Particular requirements for d.c. or a.c. supplied electronic controlgear for LED modules
EN 62471	Photobiological safety of lamps and lamp systems
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)



Product Drawing

