

DOCUMENTO TÉCNICO

303DOWELL ESPARRAGO DOBLE ROSCA

IT
rev. 11/2016

1. DATOS DE INSTALACION

1.1 303D

Esparrago de doble rosca



Dimensiones						
ØM	L1	ØD	L2	L3	SW	Huella
M6	38,5 ÷ 40,5	5,75 ÷ 6,05	11 ÷ 13	23 ÷ 25	--	Hexalobular Tx15
	48,5 ÷ 50,5		15 ÷ 17	27 ÷ 30		
	58 ÷ 61		17 ÷ 19	33 ÷ 36		
	68 ÷ 71		25 ÷ 27			
	78 ÷ 81		33 ÷ 35			
M8	48,5 ÷ 51	6,85 ÷ 7,15	12 ÷ 14	28 ÷ 31	--	Hexalobular Tx25
	58,5 ÷ 61		14 ÷ 16	36 ÷ 39		
	68,5 ÷ 71		24 ÷ 26			
	78 ÷ 81		27 ÷ 30	46 ÷ 49	5,85 ÷ 6,00	
	88 ÷ 91		32 ÷ 35			
	98 ÷ 101		40 ÷ 45			
	108 ÷ 111		48 ÷ 52			
	118 ÷ 121					
128 ÷ 131	8,75 ÷ 9,15	16 ÷ 20	45 ÷ 48	7,85 ÷ 8,00		
78 ÷ 81		22 ÷ 26	55 ÷ 59			
98 ÷ 101		36 ÷ 40				
108 ÷ 111		43 ÷ 47				
118 ÷ 121		48 ÷ 52				
128 ÷ 131						
138 ÷ 141						
148 ÷ 151						
178 ÷ 181						
198 ÷ 201						

PLANO

