

## LINTERNA GIRATORIA RECARGABLE USB CON POWERBANK

### Características de Producto

- Incorpora Powerbank USB de 2000mAh para dispositivos de carga.
- 2 modos iluminación de trabajo.
- Cuerpo resistente y duradero.
- Fijación múltiple, gancho plegable de 360°.
- Base magnética orientable y 360° de rotación.
- Batería de 3 horas de duración a máxima potencia.
- Se suministra con cable de carga USB.



| CAT NO.   | LUMINARIA (LÚMENES) | POTENCIA (W) | EFICIENCIA (Lm/W) | TIEMPO DE CARGA | PESO (kg) | CRI | RATIO IK | TIPO BATERÍA | CAPACIDAD BATERÍA | RANGO TEMP. (°C) | TEMP.AMBIENTE V.UTIL (°C) |
|-----------|---------------------|--------------|-------------------|-----------------|-----------|-----|----------|--------------|-------------------|------------------|---------------------------|
| LILT30R65 | 300                 | 3            | 100               | 3.5hrs          | 0.28      | >80 | IK05     | 3.7V Li-Ion  | 2000mAh           | 0 +25            | 25                        |

### Dimensiones



| NORMATIVA         | DESCRIPCIÓN                                                                                                                                                                                                |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EN 60598-1        | Luminaires – General requirements                                                                                                                                                                          |
| EN 60598-2-4      | Luminaires – Portable                                                                                                                                                                                      |
| EN 61000-3-2      | Electromagnetic compatibility (EMC) - Part 3-2: Limits - for harmonic current emissions                                                                                                                    |
| EN 61000-3-3      | Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection |
| EN 55015          | Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment                                                                                        |
| EN 61547          | Equipment for general lighting purposes - EMC immunity requirements                                                                                                                                        |
| 2002/96/EC        | Waste Electrical & Electronic Equipment (WEEE)                                                                                                                                                             |
| 2011/65/EU        | Restriction of the use of certain Hazardous Substances in EEE (RoHS)                                                                                                                                       |
| (EC) No 1907/2006 | The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)                                                                                                                           |

