


ECO SLIMLINE TRÍPODES LUZ DE TRABAJO

Características de Producto

- IP65 para entornos externos.
- Interruptores estancos individuales.
- Chips LED de alta eficiencia y larga vida.
- Suministrado con 3m de cable H05RN-F.
- Estructura ligera de acero de altura regulable y base multiposición.
- Encendido independiente.



CAT NO.	LUMINARIA (LUMENES)	POTENCIA (W)	EFICIENCIA (Lim/W)	PESO (kg)	DIMENSIONES (mm)	CRI	RATIO IK	TENSIÓN DE ALIMENTACIÓN	FRECUENCIA DE ALIMENTACIÓN (Hz)	RANGO TEMP. (°C)	L/B VIDA UTIL
EFLDTS10B50	800	10	80	2,38	790x790x1350	>80	IK06	220 - 240	50	-20 +25	L90/B10
EFLDTS30B50	2400	30	80	2,68	790x790x1370	>80	IK06	220 - 240	50	-20 +25	L90/B10
EFLDTS50B50	4000	50	80	3,10	790x790x1400	>80	IK06	220 - 240	50	-20 +25	L90/B10
EFLDTT20B50	1600x2	10x2	80	3,95	860x860x1670	>80	IK06	220 - 240	50	-20 +25	L90/B10
EFLDTT30B50	2400x2	30x2	80	4,10	860x860x1690	>80	IK06	220 - 240	50	-20 +25	L90/B10
EFLDTT50B50	4000x2	50x2	80	5,09	860x860x1710	>80	IK06	220 - 240	50	-20 +25	L90/B10



NORMATIVA	DESCRIPCIÓN
EN 60598-1	Luminaires – General requirements
EN 60598-2-4	Luminaires – Portable
EN 61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits - for harmonic current emissions
EN 61000-3-3	Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes - EMC immunity requirements
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

