

G18082 FOREST BOM

Item	Accessory name	Accessory materials/specifi	Unit	Qua	Remark
1	G25202 Diffuse cover	Light diffusion PC (CM4272-DHX) is far away from 140HUV testing	piece	1	
2	Φ210XΦ3 Foam silicone ring	Φ3 Foam silicone ring White	piece	1	
3	M3*5 Eleven -character groove head squeeze screws	Hardness is 450HV0.3, surface galvanized	piece	4	Fixed LED module
4	G18082 M3 Screw set	PC(white)	piece	4	
5	G18082-FGL-MZ-2835-D Module	0.8MM PCB plate 4000K	piece	1	
6	G25202 Wall lamp body	ADC12	piece	1	Plastic
7	M5*12 Inner hexagonal cone end tight screw	Stainless steel 304	piece	2	Spray paint color with the same lamp body, fix
8	M5*10 Inner hexagonal cone end tightly screw	Stainless steel 304	piece	1	Spray paint color with the same lamp body, fix the plastic plate
9	Ø4 Outer sawtooth lock tight pad ring	Surface galvanized	piece	2	
10	Yellow -green connection ground line (φ4) l = 140mm (word) peeling line 9mm and soaked in tin	H05V-K 1*0.75MM²	piece	1	
11	M4*8 Eleven slot head Self -squeezed screws	Hardness 450HV0.3, surface Dacromet	piece	1	Grounding
12	G18082 Inner cover sealing ring	Silicone 50 ° black	piece	1	
13	G18082 Inner cover	ABS417(black)	piece	1	
14	M3*8 Eleven slot head plate squeeze screw	Hardness 450HV0.3, surface galvanized	piece	4	Fixed inner cover
15	Ø5 thermal tube		Meter	0.03	
16	Press line buckle (4 holes)	PC black	piece	1	
17	B13.2*8 Cross Step Plate Self -attack Self -Drill Screw (no slotting at the tail)	surface galvanized	piece	2	Fixed crimping buckle
18	VDE single -core line (brown) l = 160mm (one end peels 9mm and soaked in tin, one end peels 3mm and tiny)	H05V-K 0.75mm2	piece	1	
19	VDE single -core line (blue) l = 160mm (one end peels 9mm and soaked in tin, one end peels 3mm and soaked in tin)	H05V-K 0.75mm2	piece	1	
20	Wiring terminal OJ-831 flat bottom double-press (Ojun)/PA10-10-3 double-press wiring terminal		piece	1	
21	G18082 Plastic plate	PA6+30%GF(Black)	piece	1	
22	17LG2 16476 G06444 Protective coil (black)	Silicone 50 ° black	piece	1	
	ST4.2*30 Cross recessed flat round head self tapping screws	Stainless steel 304	piece	2	Annex
	Ø6*30 Plastic expansion	φ6, HDPE	piece	2	Annex
	2.5MM Internal hexagonal wrench	Blackening	piece	1	Annex

