

Art. 4050/4051/4052/4053/4054/4055Gotas autoadhesivas protectoras
Self-adhesive protective buffers**MATERIAL**GOTA / BUFFER
ADHESIVO / ADHESIVEPOLIURETANO / POLYURETHANE
ACRÍLICO / ACRYLIC**COLOR / COLOUR**

TODOS / ALL 100% TRANSPARENTE / CLEAR

DIMENSIONES / PRODUCT SIZE

GOTA / BUFFER	<i>mod. 4050</i>	Ø8 x 2,2 mm
	<i>mod. 4051</i>	Ø12,7 x 3,5 mm
	<i>mod. 4052</i>	Ø16 x 7,9 mm
	<i>mod. 4053</i>	Ø19 x 4 mm
	<i>mod. 4054</i>	12,7 x 12,7 x 3,1 mm
	<i>mod. 4055</i>	20,5 x 20,5 x 7,6 mm

CARACTERÍSTICAS / PRODUCT FEATURES

Dureza / Hardness	ASTM-D2240	75 Shore A
Coef. Fricción (Mk)	ASTM-D1894	Acero/Steel: >1 Madera laminada/Laminated Wood: 0,9-1,4 Vidrio/Glass: >1
Abrasión / Abrasion	ASTM-C501-66	0,13 g / 1000 cyc
Tracción / Tensile	ASTM-D412-Troquel A	5,1 MPa
Dieléctrica / Dielectric	ASTM-D1000	370 volts/mm
Temperatura de Servicio	Constante/Constant	-34°C / 66°C
Service Temperature	Puntual/Intermittent	Hasta 107°C

CARACTERÍSTICAS / PRODUCT FEATURES

Gran poder de amortiguación de golpes y vibraciones
Offers impact cushioning and noise dumping
Adhesivo de base acrílica apto para múltiples superficies
Acrylic adhesive suitable in several kind of surfaces
Antideslizante, alto coeficiente de fricción
Excellent skid resistance
No mancha ni estropea las superficies
Resistance to marring and staining

